

Lockstop Primer Adhesive

Description	Sika® Lockstop Primer Adhesive is used for adhering Sika Lockstop strip-applied waterstop to concrete.																		
Where to Use	Sika® Lockstop Primer is used in conjunction with Sika® Lockstop strip-applied waterstop in nonmoving joint applications, such as retaining walls, box culverts, penetrations, concrete pipes, vaults, slabs, elevator shafts, etc.																		
Typical Data																			
Coverage	800-900 lineal feet per gallon																		
Packaging	1 gallon pails																		
Cure Mechanism	Allow the primer to dry for a minimum of 2 hours until it is tack-free.																		
	<table border="1"> <thead> <tr> <th colspan="2">Physical Properties</th> </tr> </thead> <tbody> <tr> <td>Color</td> <td>Dark brown to black (ASTM D1729)</td> </tr> <tr> <td>Odor</td> <td>Aromatic solvent order when wet, none when dry</td> </tr> <tr> <td>% Solids</td> <td>63 +/- 1 % by weight (ASTM C771)</td> </tr> <tr> <td>VOC Content</td> <td>325.4 g/L less water and exempt solvent (EPA Method 24)</td> </tr> <tr> <td>Specific Gravity</td> <td>0.89+/-0.05 g/cm³ (ASTM D297)</td> </tr> <tr> <td>Weight per Gallon</td> <td>7.4 +/-0.5 lbs/gallon</td> </tr> <tr> <td>Viscosity</td> <td>2000-4000 cps (ASTM D2196)</td> </tr> <tr> <td colspan="2">*Results may differ based upon statistical variations depending upon equipment, temperature, application methods, test methods, and actual site conditions.</td> </tr> </tbody> </table>	Physical Properties		Color	Dark brown to black (ASTM D1729)	Odor	Aromatic solvent order when wet, none when dry	% Solids	63 +/- 1 % by weight (ASTM C771)	VOC Content	325.4 g/L less water and exempt solvent (EPA Method 24)	Specific Gravity	0.89+/-0.05 g/cm ³ (ASTM D297)	Weight per Gallon	7.4 +/-0.5 lbs/gallon	Viscosity	2000-4000 cps (ASTM D2196)	*Results may differ based upon statistical variations depending upon equipment, temperature, application methods, test methods, and actual site conditions.	
Physical Properties																			
Color	Dark brown to black (ASTM D1729)																		
Odor	Aromatic solvent order when wet, none when dry																		
% Solids	63 +/- 1 % by weight (ASTM C771)																		
VOC Content	325.4 g/L less water and exempt solvent (EPA Method 24)																		
Specific Gravity	0.89+/-0.05 g/cm ³ (ASTM D297)																		
Weight per Gallon	7.4 +/-0.5 lbs/gallon																		
Viscosity	2000-4000 cps (ASTM D2196)																		
*Results may differ based upon statistical variations depending upon equipment, temperature, application methods, test methods, and actual site conditions.																			
How to Use																			
Surface Prep	When applying to concrete, all surfaces shall be fully cured and dry. Prepare the application area by removing all loose particles and dirt.																		
Application	<ul style="list-style-type: none"> ■ Apply by brushing a strip of Lockstop Primer Adhesive slightly wider than the Lockstop waterstop profile. A 2" wide strip is typically sufficient. ■ Lockstop Primer Adhesive and Lockstop waterstop should be applied the same day. 																		
Limitations	Only for use in non-moving concrete construction joints.																		
Shelf Life	12 months when stored in the unopened, original packaging in warehouse conditions.																		
Storage	After the container has been initially opened, maintain a tight seal at room temperature not to exceed 90°F.																		
Product Conditioning	Temperature not to exceed 90°F.																		

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sika Greenstreak Sales Office
3400 Tree Court Industrial Blvd.
St. Louis, MO 63122
Tel: (800) 325-9504
Fax: (800) 551-5145
usa.sika.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: (201) 933-8800
Fax: (201) 933-6225
usa.sika.com

Sika Canada Inc.
601, Delmar Avenue
Pointe-Claire, QC H9R 4A9
Phone: (514) 697-2610
Fax: (514) 697-3087
can.sika.com



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.