



## PRODUCT DATA SHEET

# SCOFIELD® Liquid Release BG

### Bubblegum Scented Release

#### PRODUCT DESCRIPTION

SCOFIELD® Liquid Release BG is a low-cost bubble gum scented release and bond breaker for use in the concrete stamping process. Application of SCOFIELD® Liquid Release BG to the concrete surface and stamps prior to stamping will prevent the transfer of the wet paste to the stamping mat. It may also be applied to tools to prevent them from marring patterns in fresh concrete and may be used when stamping or texturing cementitious overlays. SCOFIELD® Liquid Release BG will not damage integrally colored concrete and is suitable for use with most color hardeners. It will evaporate completely, leaving no residue, and will not interfere with the application of solvent-borne sealers. SCOFIELD® Liquid Release BG is not intended for use as a bond breaker for tilt-up construction.

#### USES

Apply over fresh concrete or overlays that will be imprinted with stamping tools.

#### PRODUCT INFORMATION

<b>Packaging</b>	5-gallon (18.9 L) pails.
<b>Shelf Life</b>	1 year in original, unopened container.
<b>Storage Conditions</b>	Do not store at temperatures below 32 degrees F (0 degrees C).

#### APPLICATION INFORMATION

<b>Coverage</b>	Concrete Surface: 200 ft <sup>2</sup> per gallon. Stamps and Tools: 400 ft <sup>2</sup> per gallon.
-----------------	---

# APPLICATION INSTRUCTIONS

any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## SURFACE PREPARATION

Tool surfaces should be clean and dry before applying SCOFIELD® Liquid Release BG. For best results, remove any dirt, rust, scale or concrete before application. Tools that have been previously treated with a neutral form release should be cleaned with detergent and warm water, then thoroughly rinsed and dried before using SCOFIELD® Liquid Release BG. Wait until the concrete surface is firm enough to support a persons weight, then apply SCOFIELD® Liquid Release BG and proceed to stamp.

## APPLICATION

SCOFIELD® Liquid Release BG should be applied to the concrete surface and the clean imprinting tool with a pump up sprayer, immediately prior to imprinting. An even, light application to both surfaces should be sufficient to prevent the transfer of paste. Since the material evaporates, it is necessary to minimize the time between application of the release material and the imprinting process. Mats and tools will need to be periodically resprayed. The evaporation rate of SCOFIELD® Liquid Release BG is affected by wind, humidity, and temperature. Avoid applying excessive amounts of the material, as this may cause defects in the concrete surface. If excess material is applied, allow to evaporate. Product leaves no residue.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

### Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



### Product Data Sheet

SCOFIELD® Liquid Release BG  
October 2018, Version 01.01  
021405011000000050

SCOFIELDLiquidReleaseBG-en-US-(10-2018)-1-1.pdf

