

## PRODUCT DATA SHEET

# SCOFIELD® Traction Additive

A clear lightweight coatings additive used to mildly texture and increase slip resistance with minimal change in appearance.

### PRODUCT DESCRIPTION

SCOFIELD® Traction Additive is a lightweight synthetic coatings additive designed to increase slip resistance with minimal changes to coating color or appearance. It is easily incorporated into water or solvent based paints, stains, and sealers just prior to application. Lighter and less abrasive than ordinary sand aggregates, settling during application is reduced, a uniform appearance is more easily achieved, and surfaces are more comfortable to walk on.

### USES

Use to improve the slip resistance of interior or exterior residential and commercial floors, stairs, ramps, pools, garages, platforms, or walkways. SCOFIELD® Traction Additive is suitable for use with all film forming Scofield products.

### CHARACTERISTICS / ADVANTAGES

- Increases slip resistance with minimal changes to coating color, gloss, or appearance.
- Mixes into most solvent or water based coatings with reduced settling during application.
- Less abrasive aggregate feels better under bare feet and is less destructive to clothing.

### PRODUCT INFORMATION

<b>Chemical Base</b>	Polypropylene Plastic Bead
<b>Packaging</b>	SCOFIELD® Traction Additive is available in 1-pound (0.45 kg) containers.
<b>Appearance / Color</b>	White powder that dries clear in most coatings.
<b>Shelf Life</b>	2 years from the date of manufacture.
<b>Storage Conditions</b>	Store unopened at 34°F - 140°F (1°C - 60°C).

### APPLICATION INFORMATION

<b>Recommended Dosage</b>	Depending upon desired texture, use one-half pound to two pounds (0.23–0.91 kg) of SCOFIELD Traction Additive with each five gallons (18.9 L) of Scofield paint, polymer stain, or sealer.
---------------------------	--

## APPLICATION INSTRUCTIONS

### EQUIPMENT

Refer to the coating instructions for proper application equipment. If spray equipment is used, filters and a tip sizes that allow SCOFIELD® Traction Additive to pass through are required.

### APPLICATION

#### Mixing

Stir into paint, stain, or sealer prior to application following manufacturer's recommendations. During use, stir periodically to ensure uniform product distribution.

#### Application

Follow manufacturer's instructions.

## AVAILABILITY/WARRANTY

### Availability

SCOFIELD® Traction Additive is marketed nationwide and inter-nationally, directly to the user through strategically located warehouses, dealers, and representatives. Contact Scofield for its nearest representative.

Scofield offers a complete line of engineered systems for coloring, texturing, and improving performance in architectural concrete. Scofield Systems address specialized requirements for interior, exterior and vertical uses with compatible systems of complementary products including coloring admixtures, color hardeners, colored cementitious toppings, stains, curing compounds, sealers, coatings, repair products and texturing tools. Visit the Scofield website at [www.scofield.com](http://www.scofield.com) for further information.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.  
VOC = 0g/l.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of Sika products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Mexicana S.A. de C.V.**

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



**Product Data Sheet**

SCOFIELD® Traction Additive  
October 2018, Version 01.01  
020816020010000015

SCOFIELDTractionAdditive-en-US-(10-2018)-1-1.pdf

