



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

### SECTION 1. IDENTIFICATION

Product name : Sika® Inject-215 Accelerator

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage : Category 1

Specific target organ toxicity - repeated exposure (Oral) : Category 2

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.  
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**  
P260 Do not breathe mist or vapors.



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

P280 Wear eye protection/ face protection.

### Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
2,2',2''-nitrilotriethanol	102-71-6		$\geq 50 - < 70$
2,2'-iminodiethanol	111-42-2	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373	$\geq 5 - < 10$

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

- In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No known significant effects or hazards.  
Excessive lachrymation  
Causes serious eye damage.  
May cause damage to organs through prolonged or repeated exposure if swallowed.
- Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
 Do not get in eyes, on skin, or on clothing.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2',2''-nitrilotriethanol	102-71-6	TWA	5 mg/m <sup>3</sup>	ACGIH
2,2'-iminodiethanol	111-42-2	TWA (Inhalable fraction and vapor)	1 mg/m <sup>3</sup>	ACGIH
		TWA	3 ppm 15 mg/m <sup>3</sup>	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : light yellow
- Odor : amine-like
- Odor Threshold : No data available
- pH : ca. 11
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 214 °F / 101 °C  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

flammability limit

Vapor pressure : 23 hpa

Relative vapor density : No data available

Density : ca. 1.1 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-  
octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds  
(VOC) content : 62 g/l  
A+B+C Combined

52 g/l  
Sika® Inject-215 Accelerator + Sika® Injection-310 US Com-  
bined.

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-  
tions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition  
products : No decomposition if stored and applied as directed.



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Not classified due to lack of data.

#### **Skin corrosion/irritation**

Not classified due to lack of data.

#### **Serious eye damage/eye irritation**

Causes serious eye damage.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

Not classified due to lack of data.

##### **Respiratory sensitization**

Not classified due to lack of data.

##### **Germ cell mutagenicity**

Not classified due to lack of data.

##### **Carcinogenicity**

Not classified due to lack of data.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans 2,2'-iminodiethanol	111-42-2
-------------	--	----------

<b>OSHA</b>	Not applicable
-------------	----------------

<b>NTP</b>	Not applicable
------------	----------------

##### **Reproductive toxicity**

Not classified due to lack of data.

##### **STOT-single exposure**

Not classified due to lack of data.

##### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if swallowed.

##### **Aspiration toxicity**

Not classified due to lack of data.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

##### **Components:**

##### **2,2'-iminodiethanol:**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 55 mg/l



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

aquatic invertebrates : Exposure time: 48 h  
Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 75 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally Hazardous Substance, liquid, n.o.s.  
(2,2'-iminodiethanol)





## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

Class : 9  
Packing group : III  
Labels : CLASS 9  
Marine pollutant : no

As per 49CFR 171.8, the product is classified as a Hazardous Substance if the shipping contents (in a single package) exceed: 110 gallons

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)
2,2'-iminodiethanol	111-42-2	100

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Specific target organ toxicity (single or repeated exposure)  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2,2'-iminodiethanol	111-42-2	>= 5 - < 10 %
---------------------	----------	---------------

### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):  
2,2'-iminodiethanol 111-42-2 >= 5 - < 10 %

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including 2,2'-iminodiethanol, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## Sika® Inject-215 Accelerator

Revision Date 10/05/2023

Print Date 10/24/2023

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
ACGIH / TWA	:	8-hour, time-weighted average
OSHA P0 / TWA	:	8-hour time weighted average

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 10/05/2023

100000034914  
US / Z8