

## **BUILDING TRUST**

## PRODUCT DATA SHEET

# UltraCure DOT

Single-Use Wet Curing Blankets for DOT and Pervious Applications

#### PRODUCT DESCRIPTION

UltraCure DOT is a single-use wet curing blankets provide constant and thorough hydration while maintaining a 100% relative humidity condition on the slab for a curing period of 14 days resulting in less surface discoloration and more evenly cured concrete.

#### **USES**

Concrete slabs-on-ground requiring a 14 day curing period.

Typical structures include:

- Warehouse / Distribution Centers
- Big Box Stores
- Manufacturing Facilities
- Commercial / Industrial Complexes
- Chemical Containment Storage Areas
- Water / Wastewater Treatment Structures
- Entertainment Centers
- Decorative Concrete Applications
- Bridge Decks and Concrete Paving
- Parking Lots and Site Paving
- Airports

## **CHARACTERISTICS / ADVANTAGES**

- Absorbs and distributes water evenly over the entire concrete surface
- Maintains 100% relative humidity on the slab for a minimum of 14 days
- Reduction of material, labor, re-wetting time, storage, and transportation costs that are involved when using traditional wet cure methods
- Increases concrete strength and durability
- Reduces permeability of concrete, cracking, crazing, dusting, and efflorescence
- Improves abrasion resistance
- Helps prevent plastic shrinkage cracking
- Meets or exceeds requirements of ASTM C171-03, ASTM C171-97a, and AASTO M171-00

## PRODUCT INFORMATION

Packaging	Sika® UltraCure DOT™ rolls are shrink wrapped in a clear poly covering and stacked four (4) wide by eight (8) high on a wooden pallet that will have the overall dimensions of forty four (44) inches wide by ninety six (96) inches long. 384 rolls fit onto a truck (12 pallets). One roll of Sika® UltraCure DOT™ weighs 50 lbs. One pallet of Sika® UltraCure DOT™ weighs 2,000 lbs. Coverage: 800 ft2 per roll (8 ft wide x 100 ft long roll)
Shelf Life	18 months
Storage Conditions	No special safety measures required. Store in a dry location away from open

**Product Data Sheet** 

**UltraCure DOT**August 2024, Version 01.02
020703830200000029

#### **BASIS OF PRODUCT DATA**

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## **AVAILABILITY/WARRANTY**

Consult a Sika® Greenstreak® engineer to review your specific project parameters, additional product information, documentation for LEED® compliance purposes, or warranty information.

## **ENVIRONMENTAL, HEALTH AND SAFETY**

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## **APPLICATION INSTRUCTIONS**

#### How to Use Cure Mechanism:

Super absorbent fibers that effectively trap water and serve as a hydrating reservoir for the slab as it cures.

#### **Surface Prep:**

Remove any debris and loose material from the concrete surface to be cured.

#### **APPLICATION METHOD / TOOLS**

Place Sika® UltraCure DOT™ wet cure covering in widest practical width as soon as concrete has hardened sufficiently to prevent surface damage. Edges and ends shall be lapped 4"- 6". Install Sika® UltraCure DOT™ moisture containing wet cure covering material as per manufacturer's written instructions as soon as practical and while the surface of the concrete is still moist. After blanket installation on slab surface, wet top surface of

perforated curing blanket with 1/8" to 1/4" inch of water to cover entire surface area of blanket. Monitor surface temperature of concrete and continue to apply curing water to the top of the curing blanket until concrete surface is within 15 degrees of ambient temperature. No portion of this product shall be re-used once it has been put into use on a slab on grade or other concrete application.

Maintain Sika® UltraCure DOT™ in place on concrete for a period of not less than seven (7) days and up to (14) days after placement. Continuous inspection for the purpose of maintaining 100 % curing blanket contact with surface to be cured is recommended using appropriate restraints placed to keep the material in place for outside use where wind could be an issue. Periodic monitoring of moisture retention in the curing blanket is recommended and additional water should be applied if required.

#### Removal

Pick up the blankets and properly dispose of them after the 14 day curing period. If removing the blankets after an extended period of time, rewetting of the slab may be required.

#### Clean Up

Pick up the blankets and properly dispose of them after the 14 day curing period. If removing the blankets after an extended period of time, rewetting of the slab may be required.

#### First Aid

This product is an inert solid. First aid is normally not required. Seek medical attention if ingested.

#### OTHER RESTRICTIONS

See Legal Disclaimer.

#### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY



**UltraCure DOT**August 2024, Version 01.02
020703830200000029



#### FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF **MERCHANTABILITY OR FITNESS FOR A PARTICULAR** PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/group/SikaCorp/termsandconditions.html or by calling 1-800-933-7452.

#### Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: +1-800-933-7452 Fax: +1-201-933-6225 usa.sika.com



Product Data Sheet UltraCure DOT August 2024, Version 01.02 020703830200000029 UltraCureDOT-en-US-(08-2024)-1-2.pdf

