



# SikaBond®-T55

## ADHESIVE FOR SOLID WOOD FLOORING

- Bonds to difficult woods
- Fast curing - sand & finish in 12 hours
- Bonds super wide solids

BUILDING TRUST



# SikaBond®-T55 ADHESIVE FOR SOLID WOOD FLOORING

SikaBond-T55 is a one-component, low-VOC, highly elastic, crack bridging, super strong polyurethane adhesive for full surface bonding of wood flooring and ceramic tiles.

## FEATURES AND BENEFITS

- 400% elongation
- Extremely easy to trowel
- Fast curing - floors can be sanded after 12 hours of cure
- Crack bridging
- Compatible with problematic woods
- Suitable for in-floor radiant heat installations
- Excellent "green grab"
- Footfall-sound-dampening adhesive



## FOR MORE SikaBond® INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452), Website [www.usa.sika.com](http://www.usa.sika.com)



RESPONSIBLE CARE  
OUR COMMITMENT TO SUSTAINABILITY



ISO 9001  
Certificado # FM 89711  
RC 14001  
Certificado # RC 51039

Can contribute 1 LEED® point per installation

SIKA CORPORATION  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201 933 8800  
800 933 SIKA  
Fax: 201 933-6225

SIKA CANADA, INC.  
601 Delmar Avenue  
Quebec H9R4A9  
Phone: 514 697 2610  
Fax: 514 694 3087

SIKA MEXICANA S.A. DE C.V.  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537

BUILDING TRUST

