

PAINABLE WHILE WET



SikaHyflex[®]-150 LM

ONE-COMPONENT, LOW MODULUS, HYBRID CONSTRUCTION SEALANT

- Paintable immediately after application
- 60 min skin time
- Excellent for sealing vinyl windows
- +/- 50% joint movement capability (ASTM C719)
- White stays white
- Commonly used on stucco, concrete, EIFS and brick surfaces

Available in

Cartridge
300 ml

Unipack
600 ml



BUILDING TRUST



SikaHyflex[®] -150 LM

PRODUCT INFORMATION

APPLICATIONS

- ▲ For joints or gaps connecting dissimilar substrates - e.g. vinyl to concrete, aluminum to EIFS.
- ▲ Window Perimeter
- ▲ Expansion joints
- ▲ Curtain Wall Construction
- ▲ For applications that require both paintability and adhesion to non-porous substrates
- ▲ User friendly in cold temperature applications

ADVANTAGES

- ▲ Fast skin time
- ▲ Multi-substrate adhesion
- ▲ Superior UV resistance and weathering
- ▲ Color retention - white stays white
- ▲ Can be over-painted soon after application (once skin has formed)
- ▲ Very low VOC < 12g/L
- ▲ Non-staining

TYPICAL DATA

- ▲ Meets ASTM C920, Class 50
- ▲ VOC 12 g/L
- ▲ Shore A: 27
- ▲ Non Staining
- ▲ Excellent weathering and UV resistance
- ▲ Shelf Life 12 months
- ▲ Elongation: 1000%
- ▲ Skin Time: 60 min +/-
- ▲ Paintable immediately after application

PACKAGING

- ▲ 10.1 oz cartridges (24 per case)
- ▲ 20 oz sausages (20 per case)

AVAILABLE COLORS

- ▲ White
- ▲ Off-White
- ▲ Limestone
- ▲ Tan
- ▲ Stone
- ▲ Aluminum Gray
- ▲ Redwood Tan
- ▲ Medium Bronze
- ▲ Special Bronze
- ▲ Black

* For up to date and accurate information please consult the current Technical Data Sheet at usa.sika.com

Note: Advice on specific applications is available from the Technical Service Department of Sika Construction Products Division.

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.usa.sika.com

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

