

SikaProof® A

Fully Bonded FPO Sheet Membrane Waterproofing System for Basement and other Below Grade Structures

Description	SikaProof® A is a fully and mechanically bonded, composite sheet membrane waterproofing system. It consists of an embossed, flexible polyolefin (FPO) membrane laminated with a sealant grid and a non-woven fleece. SikaProof® A is cold-applied and pre-applied, as it is installed without heat or open flames, and before the steel reinforcement is placed and the concrete is poured.
Where To Use	Damp-proofing, concrete protection and waterproofing for basements and other below grade concrete structures against ground water ingress: <ul style="list-style-type: none"> ■ Below grade concrete slabs ■ Below grade walls with both single (blindsided forming) and double-faced formwork (open cut) ■ Additions and retrofitting work ■ For prefabricated construction
Advantages	<ul style="list-style-type: none"> ■ Cold-applied (no pre-heating or open flames) and pre-applied, before the reinforcement is placed and the concrete is poured. ■ Fully bonded to the concrete structure. ■ No lateral water underflow or migration is possible between the concrete and the membrane when installed in accordance with Sika® Greenstreak™'s Instructions. ■ High watertightness determined in accordance with ASTM test standards. ■ Easy to install with fully adhered joints (no welding required). ■ Weather resistant with temporary UV-stability during installation. ■ High durability. ■ High tensile strength and elongation. ■ High flexibility and crack-bridging ability. ■ Resistant to aggressive mediums in natural ground water and soil. ■ Can be combined with other approved Sika® waterproofing systems including: <ul style="list-style-type: none"> ■ SikaProof® P post applied membranes ■ Sikaplan® WT membranes, FPO-based sheet waterproofing membranes ■ Sikadur®-Combiflex SG system, FPO-based joint sealing system ■ SikaBit® S-60 self-adhered membranes
Typical Data	
Coverage	<p>SikaProof® A-05: 30 sm (323 sf) or 60 sm (646 sf) per roll</p> <p>SikaProof® A-08: 25 sm (269 sf) or 50 sm (538 sf) per roll</p> <p>SikaProof® A-12 20 sm (215 sf) or 40 sm (430 sf) per roll</p>
Appearance	Light yellow sheet membrane, laminated with a fleece layer
Packaging	SikaProof® A Edge rolls are wrapped individually in a yellow PE-foil.



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

Waterproofing

	Total Thickness	Roll Width	Roll Length
SikaProof® A-05	1.00 mm (0.05 in.)	1 m or 2 m (3.28 ft. or 6.56 ft.)	30 m (98 ft.)
SikaProof® A-08	1.25 mm (0.05 in.)	1 m or 2 m (3.28 ft. or 6.56 ft.)	25 m (82 ft.)
SikaProof® A-12	1.60 mm (0.06 in.)	1 m or 2 m (3.28 ft. or 6.56 ft.)	20 m (65 ft.)

Technical Data

Chemical Base:

Membrane Layer:	Flexible Polyolefin (FPO)
Sealant grid:	Polyolefin (PO)
Fleece layer:	Polypropylene (PP)

Mass per unit area:

SikaProof® A-05	0.90 kg/m ² (0.16 lb/ft ²)	-5 / +10%
SikaProof® A-08	1.15 kg/m ² (0.24 lb/ft ²)	-5 / +10%
SikaProof® A-12	1.50 kg/m ² (0.31 lb/ft ²)	-5 / +10%

Thickness: ASTM D3767

	Total Thickness	Membrane Thickness	Deviation
SikaProof® A-05	1.00 mm (0.04 in.)	0.50 mm (0.02 in.)	-5 / +10%
SikaProof® A-08	1.25 mm (0.05 in.)	0.80 mm (0.03 in.)	-5 / +10%
SikaProof® A-12	1.60 mm (0.06 in.)	1.20 mm (0.05 in.)	-5 / +10%

Property	Value	ASTM Test Method
Tensile Strength	TD: 1100 psi MD: 1200 psi	ASTM D412
Elongation	TD: 800% min. MD: 700% min.	ASTM D412
Peel Adhesion to Concrete	55 lbs/in	ASTM D903
Lap Peel Adhesion	50 lbs/in	ASTM D1876
Water vapor transmission	3.45 X 10 ⁻⁹ g/Pa·S·m ² (0.06 perms)	ASTM E96
Low temperature	Pass (no cracking @ -29°)	ASTM D1970
Puncture resistance	170 lbs	ASTM E154
Water absorption	0.032% weight gain	ASTM D570 (24 hr./23°C)
Crack Cycling	Pass (no cracking at -15F)	ASTM C836
Radon Permeability		
	SikaProof® A-08 Edge	(2.0 +/- 0.3) x 10 ⁻¹² m ² /s
	SikaProof® A-12 Edge	(5.3 +/- 0.7) x 10 ⁻¹² m ² /s
Resistance to Hydrostatic head and Lateral Water Migration:		ASTM D 5385 mod.
	SikaProof® A-08 Edge	≥7.0 bar (100 psi)
	SikaProof® A-12 Edge	≥7.0 bar (100 psi)

TD = Transverse Direction

MD = Machine Direction

* Results may differ based upon statistical variations depending upon equipment, temperature, application methods, test methods, and actual site conditions.



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

System Information

System Components:

- SikaProof® A-05, membrane in rolls of widths 1.0 or 2.0 m
- SikaProof® A-08, membrane in rolls of widths 1.0 or 2.0 m
- SikaProof® A-12, membrane in rolls of widths 1.0 or 2.0 m
- SikaProof® Tape-150, self-adhesive tape for internal jointing, based on butyl-rubber, in 150 mm width
- SikaProof® ExTape-150, self-adhesive tape for external jointing, based on butyl-rubber, in 150 mm width

Accessories:

- SikaProof® A-08 / -12 Edge, preformed sheet in L-shape, to form the waterproofing system edges, corners and connections.
- SikaProof® Patch-200, external membrane patching tape for sealing any local damage or penetrations, supplied in 200 mm width.
- SikaProof® MetalSheet, to create special details, such as pile heads.
- SikaProof® FixTape-50, for fixing and repairing around details and penetrations.

Substrate Quality:

The substrate for the SikaProof® A membrane needs sufficient stability to avoid movement during the construction activity.

A smooth, uniform and clean substrate surface is essential to prevent membrane damage. Close large gaps and voids (> 12 mm) before installation of the SikaProof® A membrane system. The substrate can be damp or slightly wet. Do not install over ponding water.

Suitable substrates to fix the SikaProof® A membrane system onto are:

- Concrete or blinding/mudslab concrete
- Well compacted soil/fill
- Formwork
- Rigid thermal insulation
- Wooden frames

How to Use

Surface Prep

The substrate for the SikaProof® A membrane needs sufficient stability to avoid movement during the construction activity.

A smooth, uniform and clean substrate surface is essential to prevent membrane damage. Close large gaps and voids (> 0.5-0.6 in) before installation of the SikaProof® A membrane system. The substrate can be damp or slightly wet. Do not install over ponding water.

Suitable substrates on which to place SikaProof® A are:

- Concrete or blinding/mudslab concrete
- Formwork
- Rigid thermal insulation
- Wooden frames

Application

Conditions/ Limitations

Substrate Temperature: +5°C min. / + 35°C max. (+40°F min./ +95°F max.)

Ambient air temperature: +5°C min. / + 35 °C max. (+40°F min./ +95°F max.)

Ambient maximum (Temperature of Liquids): +35°C groundwater (+95°F max.)

Application Instructions

Application Method: SikaProof® A is a cold-applied and pre-applied sheet membrane waterproofing system, installed before the reinforcement is placed and the concrete is poured.

The joints of SikaProof® A are fully adhered by self adhesive strips on the membrane sheet or with SikaProof® adhesive tapes rather than by welding. Only the following tools are required: tape measure, marking pen, membrane cutter and pressure roller.

Installation Procedure

1. Ensure the substrate is correctly constructed and prepared, see Method of Application - Surface Preparation.
2. Install the pre-formed SikaProof® A Edge sheet for the perimeters.



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

Waterproofing

3. Form the corners with the same pre-fabricated Edge sheet and adhere them externally with SikaProof® ExTape-150 and internally with SikaProof® Tape-150.
 4. Install the SikaProof® A membrane on the horizontal and vertical surfaces using the 1.0 or 2.0 m width rolls (as appropriate) and adhere the joints with the self adhesive strips lengthways and for cross joints using the SikaProof® Tape-150 and SikaProof® ExTape-150.
 5. Form all existing details, such as pipe penetrations, shaft connections, pits, pile heads, expansion joints and any other details using the appropriate accessory products.
 6. Finally, check all the joints, connections and details, to ensure they are correctly and fully adhered using the SikaProof® Tape-150 and SikaProof® ExTape-150.
 7. After the SikaProof® membrane system is applied the reinforcement will be placed and the concrete will be poured.
 8. After removing the formwork and any removable form ties, such as shuttering anchors, any membrane damage and any construction joints can be sealed on the external side (on the membrane) with the SikaProof® Patch-200 or the Sikadur® Combiflex SG system.
- Please refer to the SikaProof® A Method Statement for further information regarding the installation procedure.

Limitations	SikaProof® A membranes must be installed by trained and approved Sika® contractors. SikaProof® A membranes are not permanently UV stabilized and therefore cannot be installed on structures or areas permanently exposed to UV light and external weathering. The maximum UV light exposure during installation or in the final stage of SikaProof® A system is 7 weeks.
Shelf Life	Do not apply SikaProof® A membranes during continuous or prolonged rainfall. SikaProof® A membrane rolls have a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C (+40°F) and +30°C (+85°F).
Storage	SikaProof® A membrane rolls must be protected from direct sunlight, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sika Greenstreak Sales Office
3400 Tree Court Industrial Blvd.
St. Louis, MO 63122
Tel: (636) 225-9400
Fax: (636) 225-2049
usa.sika.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: (201) 933-8800
Fax: (201) 933-6225
usa.sika.com

Sika Canada Inc.
601, Delmar Avenue
Pointe-Claire, QC H9R 4A9
Phone: (514) 697-2610
Fax: (514) 697-3087
can.sika.com



Sika®

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.