

SikaQuick® EZ PATCH

FAST-SETTING MATERIAL USED FOR PATCHING OF CONCRETE SURFACES AND SLOPES

- Easy to use, one-component
- Variable water ratios for differente use: resurfacing/sloping
- Interior and exterior use
- Feather edge application

Available inBag
30 lbs.





SikaQuick® EZ PATCH

HIGH PERFORMANCE, FAST SETTING, CEMENT BASED PATCH

APPLICATIONS

- Used to reprofile substrates or subfloor surfaces from feather edge to 1-1/2" (38 mm).
- Repair minor defects, holes, cracks and pre-fill nonmoving joints and seams in concrete, balconies, terrece, etc.
- On grade, above and below grade on concrete and mortar.
- On horizontal surfaces.
- As an overlay system for topping/resurfacing concrete.

TYPICAL DATA

- Shelf Life: One year in original, unopened bags
- Storage Conditions: Store dry at 45°-95°F (7°-35°C)
- · Color: Gray powder
- Yield: 12-15 ft2 at 1/4" (1.1-1.4 m2 at 6 mm) per bag
- Waiting Time / Overcoating: 16 24 hours
- 28 days compressive strength (ASTM C-109) 4,000 psi (27.6 MPa)
- Layer Thickness Min. Max.

Neat FE 1-1/2" (38.1 mm) **Extended** 1-1/2" (38.1 mm) 3" (76.2 mm)

BENEFITS

- Easy to use, one-component.
- Variable water ratios for differente use: resurfacing/sloping.
- Interior and exterior use.
- Feather edge application.
- High compressive and flexural strengths.
- High abrasion resistance.
- Increased freeze/thaw durability.

LITERATURE

- Product Data Sheet
- Safety Data Sheet
- CSI Specification
- *Always refer to Current Product Data Sheet and SDS for detailed performance specifications prior to use.



Note: Advice on specific applications is available from the Technical Service Department of Sika Construction Products Division.

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.usa.sika.com

Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: 201-933-8800 Fax: 201-933-6225

