



SikaQuick® Smooth Finish

ULTRA-LIGHT MORTAR FOR CONCRETE REPROFILING AND PATCHING

- Ultra smooth consistency
- Easy to use and apply, just add water
- Fast finishing time, same day sanding and painting
- High bond strength ensures excellent adhesion
- Suitable for interior and exterior applications
- Easy to trowel - Contractor friendly

Available in
Bag
50 lbs (22.7 kg)



BUILDING TRUST



SikaQuick® Smooth Finish

FOR CONCRETE REPROFILING AND PATCHING

APPLICATIONS

- Tilt up panels
- Pre cast concrete
- Cast in place concrete
- Concrete block
- Masonry

TYPICAL DATA

Application Time Approximately 30 minutes

Finishing Time 1 hour

Lift Height Max 1/2" Min: FE

Time Between Lifts After final set

Compressive Strength (ASTM C-109) psi

▪ 24 hours 1000 psi

▪ 28 days >2000 psi

Bond Strength, psi - Direct Tensile (IRCI No. 210.3)

Substrate failure >250



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikausa.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



RESPONSIBLE CARE
OUR COMMITMENT TO SUSTAINABILITY



BUILDING TRUST

