



Sikaflex® Crack Flex Sealant

One-component, textured polyurethane



One-component, textured polyurethane for sealing cracks in horizontal concrete and masonry surfaces. Ideal for sidewalks, garages, patios, decks, etc.



Advantages

- For cracks up to 1" wide
- Water immersible
- Elasticity allows for crack movement
- Gradually self levels
- Textured for added density
- Waterproof after cure
- Superior durability

Typical Data

Shelf Life : 1 year in original unopened packaging

Storage Conditions : Store at 40°-95°F (4°-35°C). Condition material to 65°-75°F before using.

Color : Textured Gray

Application Temperature : -40°F -100°F

Cure Time : Tack-free time: 1 to 2 hours. Final cure: 3 to 5 days

Weathering Resistance : Excellent



SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225
Toll Free : 800.933.SIKA
usa.sika.com

SIKA CANADA INC.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

SIKA MEXICANA S.A. DE C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

BUILDING TRUST

