

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex SL 1 gray Formerly MSeal SL 1 gray
Product code : 000000000050452740

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use


Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

FLAMMABLE LIQUIDS : 4
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Carcinogenicity : 2
Reproductive toxicity : 2
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H227 Combustible liquid.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P260 Do not breathe dust or mist.
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P202 Do not handle until all safety precautions have been read and understood.
P284 In case of inadequate ventilation wear respiratory protection.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314 Get medical advice/ attention if you feel unwell.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.
P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Chemical nature : Sealant

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	> 25 - < 50
Titanium dioxide	13463-67-7	>= 3 - < 5
calcium oxide	1305-78-8	>= 1 - < 3
Stoddard solvent	8052-41-3	>= 1 - < 3
toluene-2,6-diisocyanate	91-08-7	>= 0.3 - < 1
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	>= 0.2 - < 0.3
4-toluenesulphonyl isocyanate	4083-64-1	>= 0.1 - < 0.2
carbon black	1333-86-4	>= 0.1 - < 0.2
2-ethylhexanoic acid	149-57-5	> 0 - < 0.1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Product is not explosive.
- Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
-

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Conditions for safe storage : no smoking
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Designation (Inhalable fraction and vapor)		ACGIHTLV
		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		C	0.02 ppm 0.14 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	0.001 ppm	ACGIH

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
 Date of first issue: 07/30/2020

		and vapor)		
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
2-ethylhexanoic acid	149-57-5	TWA value (Inhalable fraction and vapor)	5 mg/m3	ACGIHTLV
		TWA (Inhalable fraction and vapor)	5 mg/m3	ACGIH
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car-	NIOSH REL

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
 Date of first issue: 07/30/2020

			bonate)	
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aro- matic hydrocar- bons (PAH))	NIOSH
		TWA (Inhal- able particu- late matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm	OSHA P0

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

			525 mg/m3	
--	--	--	-----------	--

Engineering measures : Provide adequate exhaust ventilation to control work place concentrations.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : gray

Odor : mild

Odor Threshold : No data available

pH : No data available

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : approx. 185.00 °F / 85.00 °C

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Method: Standard Method of Test for Flash Point by Setaflash Closed Tester, closed cup

- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : No applicable information available.
- Self-ignition : not self-igniting
- Upper explosion limit / Upper flammability limit : No applicable information available.
- Lower explosion limit / Lower flammability limit : No applicable information available.
- Vapor pressure : No applicable information available.
- Relative vapor density : No applicable information available.
- Relative density : No applicable information available.
- Density : approx. 1.3200 g/cm³ (77.00 °F / 25.00 °C)
- Solubility(ies)
 - Water solubility : No data available
 - Solubility in other solvents : No applicable information available.
- Partition coefficient: n-octanol/water : No applicable information available.
- Autoignition temperature : not determined
- Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.
- Viscosity
 - Viscosity, dynamic : No applicable information available.
 - Viscosity, kinematic : No applicable information available.
- Oxidizing properties : Not an oxidizer.
- Sublimation point : No applicable information available.
- Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Possibility of hazardous reactions : No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

calcium oxide:

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

Stoddard solvent:

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)
Method: Partition coefficient (n-octanol/water), HPLC method.

toluene-2,6-diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 3.74
Method: other (calculated)

trimethoxy(3-(oxiranylmethoxy)propyl)silane:

Partition coefficient: n-octanol/water : log Pow: -0.915
Method: other (calculated)
Remarks: unmeasurable

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

4-toluenesulphonyl isocyanate:

Partition coefficient: n-octanol/water : log Pow: 0.6 (86 °F / 30 °C)
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

carbon black:

Partition coefficient: n-octanol/water : Remarks: not applicable

2-ethylhexanoic acid:

Partition coefficient: n-octanol/water : log Pow: 2.7 (77 °F / 25 °C)
pH: 4.7
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: no

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
Date of first issue: 07/30/2020

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate	91-08-7
--------------------------	---------

US State Regulations

Pennsylvania Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Di-isononylphthalate	28553-12-0
Stoddard solvent	8052-41-3

New Jersey Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Stoddard solvent	8052-41-3
toluene-2,6-diisocyanate	91-08-7
carbon black	1333-86-4

California Prop. 65

WARNING: This product can expose you to chemicals including toluene-2,6-diisocyanate, which is/are known to the State of California to cause cancer, and methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information


SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray




Version 1.0 Revision Date: 07/30/2020 SDS Number: 000000727822 Date of last issue: -
 Date of first issue: 07/30/2020

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / Skin Designation : Skin Designation:
- ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / STEL : Short-term exposure limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-1 / C : Ceiling

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/30/2020	000000727822	Date of first issue: 07/30/2020

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/30/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED

SAFETY DATA SHEET

Sikaflex SL 1 gray Formerly MSeal SL 1 gray



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/30/2020	000000727822	Date of first issue: 07/30/2020

WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN