



SECTION 1. IDENTIFICATION

Product name : Sikalastic®-735 AL

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 1B

Carcinogenicity (Inhalation) : Category 1A

Carcinogenicity : Category 1B

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

Specific target organ toxicity : Category 1 (Lungs)
- repeated exposure

GHS label elements



Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	<p>H226 Flammable liquid and vapor. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H340 May cause genetic defects. H350 May cause cancer. H350 May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.</p>
Precautionary Statements	:	<p>Prevention:</p> <p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 Wear respiratory protection.</p> <p>Response:</p> <p>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.</p>



P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixtures****Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Isophorondiisocyanate homopolymer	53880-05-0	Acute Tox. 4; H332 Skin Sens. 1B; H317 STOT SE 3; H335	$\geq 50 - < 70$
Solvent naphtha (petroleum), light arom.	64742-95-6	Muta. 1B; H340 Carc. 1B; H350 Asp. Tox. 1; H304	$\geq 10 - < 20$
Quartz (SiO ₂) >5 μ m	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	$\geq 10 - < 20$
n-butyl acetate	123-86-4	Flam. Liq. 3; H226 STOT SE 3; H336	$\geq 1 - < 5$
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Acute Tox. 1; H330 Skin Corr. 1C; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.



	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: Asthmatic appearance Cough Respiratory disorder Allergic reactions Headache irritant effects sensitizing effects carcinogenic effects May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause genetic defects. May cause cancer. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure.
Notes to physician	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: Water
Further information	: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must



be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.



Conditions for safe storage : Prevent unauthorized access.
 Store in original container.
 Keep in a well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Store in accordance with local regulations.

Materials to avoid : Explosives
 Oxidizing agents
 Poisonous gases
 Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂) >5µm	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
n-butyl acetate	123-86-4	TWA	150 ppm 710 mg/m ³	OSHA Z-1



		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0.005 ppm	OSHA P0
		STEL	0.02 ppm	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	pigmented
Odor	:	aromatic
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	248 °F / 120 °C
Flash point	:	113 °F / 45 °C (Method: Tag closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	1.0 %(V)
Vapor pressure	:	4.9996 hpa
Relative vapor density	:	No data available
Density	:	ca. 9.69 lb/gal
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	415 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. > 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available



Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	238 g/l 226 g/l Sikalastic® 735 AL + Sikalastic® 700 ACL Combined.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if inhaled.

Components:**Isophorondiisocyanate homopolymer:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist



Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO ₂)	14808-60-7
	(Silica dust, crystalline)	
	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide (> 10 µm)	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4
OSHA	OSHA specifically regulated carcinogen	
	Quartz (SiO ₂)	14808-60-7
	(crystalline silica)	
NTP	Known to be human carcinogen	
	Quartz (SiO ₂)	14808-60-7
	(Silica, Crystalline (Respirable Size))	

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Further information

Product:



Remarks : Carbon black (1333-86-4)
Animal Toxicity:
Rat, oral, duration 2 year
Effect: no tumors

Mouse, oral, duration 2 years
Effect: no tumors
Mouse, dermal, duration 18 months
Effect: no skin tumors
Rat, inhalation, duration 2 years
Target organ: lungs
Effect: inflammation, fibrosis, tumors

Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions. Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plant studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010). Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington. Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

IARC CANCER CLASSIFICATION: In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This



conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

ICGIH CANCER CLASSIFICATION: Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

ASSESSMENT: Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.



SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Isophorondiisocyanate homopolymer:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

n-butyl acetate:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III



Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
 Proper shipping name : PAINT
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Domestic regulation**49 CFR**

UN/ID/NA number : UN 1263
 Proper shipping name : Paint
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated.

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)



Acute toxicity (any route of exposure)
 Respiratory or skin sensitization
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)
 Germ cell mutagenicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Quartz (SiO₂) >5µm, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER

Safety Data Sheet

Sikalastic®-735 AL



Revision Date 05/22/2023

Print Date 05/22/2023

ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 05/22/2023

000000604685

US / Z8