

3G Epoxy and Hybrid Acrylic High-Strength Anchoring Adhesives



3G Adhesive Family

Bonded by versatility.

3G Epoxy and Hybrid Acrylic High-Strength Anchoring Adhesives

Adhesive Anchorage Solutions



We offer the most versatile adhesive products with ultimate bonding strength. Our epoxy and hybrid acrylic adhesives perform in a wide range of temperatures and in variable conditions, allowing you to specify the right adhesive that will keep your job moving.



SET-3G™ High-Strength Epoxy Adhesive

- For threaded rod and rebar
- Exceptional performance — superior bond strengths
- Approved for dry, water-saturated, water-filled holes and submerged (underwater) installations in base materials with temperatures between 40°F (4°C) and 100°F (38°C)
- NSF/ANSI/CAN Standard 61 approved



AT-3G™ High-Strength, Hybrid Acrylic Adhesive

- For threaded rod and rebar
- Excellent for use in cold-weather conditions or applications where fast cure is required
- Approved for dry, water-saturated or water-filled holes in base materials with temperatures between 23°F (-5°C) and 104°F (40°C)
- NSF/ANSI/CAN Standard 61 approved



ET-3G™ Epoxy Adhesive

- For threaded rod and rebar
- Ideal for general doweling and threaded rod applications
- Use in base materials with temperatures between 50°F (10°C) and 110°F (43°C)
- NSF/ANSI/CAN Standard 61 approved



SET-3G — Column Installation



AT-3G Threaded Rod — Post Installation



ET-3G Rebar Installation

Products	Concrete Temperature	Tested Base Materials				Accessories
		Concrete	CMU – Grout-Filled	CMU – Hollow	URM	Required Brush
 SET-3G	40–100°F	ESR-4057	ESR-4844	ESR-4844		Wire ETBS
 AT-3G	23–104°F	ESR-5026				Wire ETBS
 ET-3G	50–110°F	ESR-5334	ESR -5309	ESR-5309	ER-870	Nylon ETB

For more product information, see *Anchoring, Fastening, Restoration and Strengthening Systems* catalog (C-A-2023) or visit strongtie.com.