

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET



1. Identification

Product Identification

Product Identifier: A Component RPS-752
Recommended Use: RPS-752 is a two-component, epoxy bonding agent for use for concrete maintenance.
Use Restrictions: For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588 USA
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada) / 1-352-323-3500 (International)
For most current SDS, please visit our website at www.strongtie.com/sds.

2. Hazard Identification

General Information

RPS-752 Epoxy Bonding Agent is a two-part system for strengthening repair bonds of newly placed repair mortars and/or concrete mixes. The two parts of this product have been assessed according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The final product will be gray in color and can be considered nonhazardous. This Safety Data Sheet covers hazards and responses for Component A. See the Component B Safety Data Sheet for complete product information.

Component A GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2A	H319: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Chronic Environmental Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritant effects. May cause rash/allergic reaction to the skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision.

GHS Label Elements



Exclamation Point Environmental Hazard

Contains: Bisphenol-A Based Epoxy Resin, Alkyl (C12-C14) glycidyl ether

Signal Word: **WARNING!**

Hazard Statements:

H315:	Causes skin irritation.
H319:	Causes serious eye irritation.
H317:	May cause an allergic skin reaction.
H411:	Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:	P201: Obtain special instructions before use.
	P202: Do not handle until all safety precautions have been read and understood.
	P261: Avoid breathing mist or vapor.
	P264: Wash thoroughly after handling.
	P272: Contaminated work clothing should not be allowed out of the workplace.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352: IF ON SKIN: Wash with plenty of water.

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET

	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before re-use.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P391:	Collect Spillage.
Storage:	P403+P235:	Store in a well-ventilated place. Keep cool.
	P405:	Store locked up.
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured A component of RPS-752. Upon combination with the B component of RPS-752 an innocuous solid coating is formed which does not present any immediate hazards. Upon grinding or cutting through the cured coating processing dust may be created. The following hazards apply to the creation and inhalation of processing dust. If deemed necessary, the use of an approved respirator, or dust mask, can be used to control exposure to dust that may occur.



Chronic Health

Health Hazard:	Carcinogenicity STOT, Repeated Exposure	Category 1A Category 2 (Lung)
Hazard Statements:	May cause cancer. May cause damage to organs (lung) through prolonged or repeated exposure (processing dust).	
Precautionary Statements:	Do not breathe dust. Do not allow dust to build up on surfaces.	

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classifications: Globally Harmonized System Classifications

The full text for H-phrases is displayed in section 16 if not above. All concentrations are in percent by weight unless otherwise noted.

Composition – All concentrations are in percent by weight unless otherwise indicated.

Chemical Name	Weight %	CAS Number	EC Number
Bisphenol A-Epichlorohydrin (Epoxy Resin)	75-95	25068-38-6	500-033-5
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411			
Alkyl (C12-C14) Glycidyl Ether	1-25	68609-97-2	271-846-8
Classifications: Skin Irrit. 2: H315, Skin Sens. 1: H317			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact:	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician immediately.
Skin Contact:	Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. If rash or irritation persists consult a physician.
Ingestion:	Rinse mouth immediately. Do not induce vomiting. Consult a physician.
Inhalation:	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

Most Important Symptoms

Irritant effects. Sensitization. Symptoms include itching, burning, redness and tearing.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Extinguish with foam, carbon dioxide, dry powder, or water fog.
Additional Information: None known.
Hazards during Fire-Fighting: Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Do not allow run-off from fire-fighting to enter drains or water courses.
Fire-Fighting Procedures: Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured): Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
Large spills (uncured): Stop the flow of material, if possible without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. Keep combustibles away from spilled material.
Cured Material: Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Pregnant women should not work with the product, if there is the least risk of exposure. When using, do not eat, drink or smoke. Do not breathe dust, mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the design limits provided by Simpson Strong-Tie.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Protect against physical damage. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection: A respirator is not required during normal use of this product in properly ventilated areas. Approved respirators should be worn when workplace conditions warrant respirator use.

RPS-752 Epoxy Bonding Agent
SAFETY DATA SHEET

General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

No exposure limits noted for components.

9. Physical and Chemical Properties

Physical State:	Liquid	Freezing/Melting Point:	N/E
Form:	Paste	Boiling Point:	>428°F (>220°C)
Color:	Clear Amber	Flash Point:	>250°F (>121°C)
Odor:	Sweet	Evaporation Rate:	N/A
Odor Threshold:	N/E	Specific Gravity:	1.13
pH:	N/E	VOC (A+B):	2 g/L
Flammability:	N/E	U/L Flammability:	N/E
Vapor Pressure:	Not Volatile	Vapor Density:	N/E
Solubility:	Insoluble	Kow:	N/E
Decomposition:	N/E	Viscosity:	N/E

10. Stability and Reactivity

Reactivity: This product is stable and non-reactive under normal conditions.
Chemical Stability: Stable under normal storage conditions.
Condition to Avoid: High heat and open flame.
Substances to Avoid: Oxidizing agents, acids, organic bases, and amines.
Hazardous Reactions: Hazardous polymerization will not occur.
Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion: Ingestion may cause irritation to the gastrointestinal tract.
Inhalation: This material is a viscous liquid to semi-solid which does not easily form vapors.
Skin contact: Causes skin irritation. May cause an allergic skin reaction.
Eye contact: Causes serious eye irritation.
Symptoms: Irritant effects. Sensitization. Symptoms include itching, burning, redness and tearing.

Information on Toxicological Effects

Acute Effects

Toxicity: Not expected to be acutely toxic.

Component	Estimate
RPS-752 Component A Toxicity Estimate	
Acute, Oral, LD50	>9000
Acute, Dermal, LC50	>2000

Skin corrosion/irritation: Causes skin irritation.
Eye damage/eye irritation: Causes serious eye irritation.
Respiratory sensitization: No data available.
Skin sensitization: May cause an allergic skin reaction.
Aspiration hazard: No data available.
Specific target organ toxicity
Single exposure: No data available.

Chronic Effects

Germ cell mutagenicity: The available data does not indicate that any components of this product present at greater than 0.1% is mutagenic or genotoxic.

RPS-752 Epoxy Bonding Agent
SAFETY DATA SHEET

Carcinogenicity: May cause cancer. The B components of this product contain components that are listed carcinogens. These components are considered carcinogens only in their inhalable form. Due to the nature of this product inhalation is highly unlikely. Exposure to respirable carcinogens is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to processing dust.

Reproductive toxicity: No data available.

Specific target organ toxicity

Repeated exposure: No data available.

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. The product is classified as toxic to aquatic life with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Estimate
RPS-752 Component A Toxicity Estimate	
Aquatic, Fish, LC50	50 mg/l, 96 hours
Aquatic, Crustacea, EC50	5 mg/l, 48 hours
Aquatic, Algae, EC50	800 mg/l, 72 hours

Persistence and degradability: This product is not expected to be readily biodegradable.

Bioaccumulative potential: No data available for this product.

Mobility in soil: This product is insoluble in water and is non-volatile.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Considerations

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Set Material: Chip or grind off surface. If you are grinding or cutting set product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust.

14. Transportation Information

RPS-752 Component A is not regulated for ground transportation by the USDOT; check specific requirements for other regions and other shipping methods.

UN number: UN3082

UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorohydrin Resin), 9, III, Marine Pollutant

Transportation Class: 9

Precautions: Other Hazard

Packing Group: III

Environment Hazard: Yes

Required Labels: 9

ERG Code (IATA): 9L

EmS (IMDG): F-A, S-F

RPS-752 Epoxy Bonding Agent
SAFETY DATA SHEET



Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: This substance/mixture is not intended to be transported in bulk.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No
SARA 311/312 Hazardous chemical: Yes
SARA 313 (TRI reporting): Not regulated.

US. California Proposition 65:

WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to www.P65Warnings.ca.gov.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Oxirane, 2-(phenoxyethyl)- (CAS 122-60-1)	Trace	2B	---	A3	CA65 (Carcinogenic)
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected CA65 – California Prop 65					

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET

Japan	One or more components in this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL)
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

16. Other Information

Date Prepared or Revised: December 2021
Supersedes: May 2020
Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

©2021 Simpson Strong-Tie Company, Inc.

Internal

FOR INTERNAL USE ONLY

A Component 752:	B Component 752:
XCOM3B	XCOM3B
	XCORR

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET



1. Identification

Product Identification

Product Identifier: **B Component RPS-752**
Recommended Use: RPS-752 is a two-component, epoxy bonding agent for use for concrete maintenance.
Use Restrictions: For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
 Pleasanton, CA 94588 USA
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada) / 1-352-323-3500 (International)
 For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

RPS-752 Epoxy Bonding Agent is a two-part system for strengthening repair bonds of newly placed repair mortars and/or concrete mixes. The two parts of this product have been assessed according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The final product will be gray in color and is considered nonhazardous. This Safety Data Sheet covers hazards and responses for Component B. See the Component A Safety Data Sheet for complete product information.

Component B GHS Classification

Classifications according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns and eye damage
	Serious Eye Damage/Irritation	Category 1	H318: Causes severe eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Reproductive Toxicity	Category 2	H361: Suspected of damaging fertility or the unborn child
	Acute Environmental Hazard	Category 1	H400: Very toxic to aquatic life
	Chronic Environmental Hazard	Category 1	H410: Very toxic to aquatic life with long lasting effects
Main Symptoms:	Damage to the eyes and skin. May cause rash/allergic reaction to the skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Long term exposure may cause chronic effects.		

GHS Label Elements



Contains: Crystalline Silica (Quartz), Polymeric cycloaliphatic amines, Tofa reaction products with TEPA
Signal Word: **DANGER!**
Hazard Statements:
 H302: Harmful if swallowed.
 H312: Harmful in contact with skin.
 H314: Causes severe skin burns and eye damage.
 H318: Causes severe eye damage.
 H317: May cause an allergic skin reaction.
 H361: Suspected of damaging fertility or the unborn child.
 H400: Very toxic to aquatic life.
 H410: Very toxic to aquatic life with long lasting effects.

RPS-752 Epoxy Bonding Agent
SAFETY DATA SHEET



Precautionary Statements:

Prevention:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P261: Avoid breathing mist or vapor.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink, or smoke when using this product.
- P271: Use only outdoor or in a well-ventilated area.
- P272: Contaminated clothing should not be allowed out of the workplace.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/clothing/eye protection/face protection.

Response:

- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
- P363: Wash contaminated clothing before reuse.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P308+P313: If exposed or concerned: Get medical attention/advice.
- P312: Call a poison center/doctor if you feel unwell.
- P370+P378: In case of fire: Use appropriate media to extinguish.
- P391: Collect spillage.
- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P405: Store locked up.
- P501: Dispose of contents/container in accordance with local/regional regulations.

Storage:

Disposal:

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured B component of RPS-752. Upon combination with the A component, an innocuous solid which does not present any immediate hazards is formed. Upon grinding or cutting through the cured product, the following hazards may apply. Ensure that good work practices, and the necessary precautionary measures, are taken to maintain safe use of the product.



Chronic Health

Health Hazard:

Carcinogenicity Category 1A
STOT, Repeated Exposure Category 2 (Lung)

Hazard Statements:

May cause cancer. May cause damage to organs (lung) through prolonged or repeated exposure (processing dust).

Precautionary Statements:

Do not breathe dust.
Do not allow dust to build up on surfaces.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classifications: Globally Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Composition – All concentrations are in percent by weight unless otherwise indicated.

Chemical Name	Weight %	CAS Number	EC Number
Crystalline Silica, Quartz Classifications: Carc. 1A: H350, STOT RE 2: H373	40-60	14808-60-7	238-878-4
Tofa, reaction products with TEPA Classifications: Acute Tox. 4: H302+H332, Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, STOT SE 3: H335	10-20	68953-36-6	273-201-6
Methyleneoxide, polymer with benzenamine, hydrogenated Classifications: Acute Tox. 4: H302, Skin Corr. 1B: H314	10-20	135108-88-2	603-894-6

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET



Tetraethylenepentamine	1-5	112-57-2	203-986-2
Classifications: Acute Tox. 4: H312, Skin Corr. 1B: H314, Eye Dam. 1: H318, Aquatic Chronic 2: H411			
Diethylenetriamine	1-5	111-40-0	203-865-4
Classifications: Acute Tox. 4: H302+H312, Skin Corr. 1B: H314, Eye Dam. 1: H318, Skin Sens. 1: H317			
Bisphenol-A	1-5	80-05-7	201-245-8
Classifications: Eye Dam. 1: H314, Skin Sens. 1: H317, Repr. 2: H361, STOT SE 3: H335			
Nonylphenol	1-5	84852-15-3	284-325-5
Classifications: Acute Tox. 4: H302, Skin Corr. 1B: H314, Repr. 2: H361, Aquatic 1: H400+H410			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Routes of Exposure

- Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician immediately.**
- Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. If rash or irritation persists **consult a physician.**
- Ingestion:** Rinse mouth immediately. Do NOT induce vomiting. **Consult a physician.**
- Inhalation:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

May cause severe irritation or burns to eyes, skin, gastrointestinal tract, and respiratory system. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dermatitis. Rash. Decreased motor functions.

5. Fire-Fighting Measures

- Suitable Extinguishing Media:** Water fog, carbon dioxide, dry chemical powder, aqueous foam.
- Additional Information:** None known.
- Hazards during Fire-Fighting:** Irritating and toxic fumes may be produced at high temperature. Hazardous gases/vapors produced are carbon monoxide, carbon dioxide, oxides of nitrogen, cyanide, aldehydes, and miscellaneous hydrocarbons. Don't allow run-off from fire-fighting to enter drains or water courses.
- Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

- Non-emergency personnel:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Local authorities should be advised if significant spillages cannot be contained.
- Emergency personnel:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

- Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
- Large spills:** Stop the flow of material, if possible without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.
- Set Material:** Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Pregnant women should not work with the product, if there is the least risk of exposure. When using, do not eat, drink or smoke. Do not breathe dust, mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the design limits provided by Simpson Strong-Tie.

Storage

Store locked up. Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Protect against physical damage. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirts/long pants and other clothing as required to minimize contact.
Respirator Protection: The use of a respirator is not required during normal use of this product in properly ventilated areas. An approved respirator should be worn whenever workplace conditions warrant respirator use, or when grinding or cutting cured product.
General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Bisphenol-A (CAS 80-05-7)	N/E	N/E	5 mg/m ³ (Inhalable Fraction)
Diethylenetriamine* (CAS 111-40-0)	N/E	1 ppm	1 ppm
Tetraethylenepentamine* (CAS 112-57-2)	1 ppm	1ppm	1 ppm (aerosol)
Tofa, reaction products with TEPA (CAS 68953-36-6)	5 ppm	5 ppm	N/E
Quartz (CAS 14808-60-7)	$\frac{10}{\%SiO_2 + 2} \text{ mg}/m^3$	0.025 mg/m ³ (respirable)	0.05 mg/m ³ (respirable)

*Skin Designation: Material can be absorbed through the skin.

9. Physical and Chemical Properties

Physical State:	Liquid	Freezing/Melting Point:	N/E
Form:	Liquid	Boiling Point:	N/E
Color:	Dark Gray	Flash Point:	266 °F
Odor:	Ammonia	Evaporation Rate:	N/E
Odor Threshold:	N/E	Specific Gravity:	1.44
pH:	N/E	Viscosity:	N/E

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET

Flammability:	N/E	U/L Flammability:	N/E
Vapor Pressure:	N/E	Vapor Density:	N/E
Solubility:	Slight	Kow:	N/E
Decomposition:	N/E	VOC (A+B):	2 g/L

10. Stability and Reactivity

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing agents and acids.
Hazardous Reactions:	Hazardous polymerization will not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Harmful if swallowed. Causes digestive tract burns.
Inhalation:	Prolonged inhalation may cause mild respiratory irritation.
Skin contact:	Harmful in contact with skin. Causes skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye damage.
Symptoms:	Corrosive effects. May cause rash/allergic reaction to skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause severe irritation or burns to the gastrointestinal tract and respiratory system.

Information on Toxicological Effects

Acute Effects

Toxicity: Harmful if swallowed. Harmful in contact with skin.

Component	Estimate
RPS-752 Component B Toxicity Estimate	
Acute, Oral, LD50	1309
Acute, Dermal, LD50	1879

Skin corrosion/irritation:	Causes severe skin burns and eye damage.
Eye damage/eye irritation:	Causes severe eye damage.
Respiratory sensitization:	No data available.
Skin sensitization:	May cause skin sensitization by contact.
Aspiration hazard:	No data available.
Specific target organ toxicity	
Single exposure:	No data available.
Chronic Effects	
Germ cell mutagenicity:	No data available.
Carcinogenicity:	May cause cancer. The B components of this product contain components that are listed carcinogens. These components are considered carcinogens only in their inhalable form. Due to the nature of this product inhalation is highly unlikely. Exposure to respirable carcinogens is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to processing dust.
Reproductive toxicity:	Components of this product are suspected of damaging fertility or the unborn child.
Specific target organ toxicity	
Repeated exposure:	May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure. May cause damage to organs (lung) through prolonged or repeated exposure (inhalation of processing dust).

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	40-60	1	KNOWN	A2	CA65
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected CA65 – California Prop 65					

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. The product is classified as very toxic to aquatic life with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Estimate
RPS-752 Component B Toxicity Estimate	
Aquatic, Fish, LC50	2 mg/l, 96 hours
Aquatic, Crustacea, EC50	5 mg/l, 48 hours

Persistence and degradability: No data available.
Bioaccumulative potential: No data available for the product.
Mobility in soil: No data available.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Considerations

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Set Material: Chip or grind off surface. If you are grinding or cutting set product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust.

14. Transportation Information

UN number: UN2735
UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylenetriamine, Nonylphenol), 8, II, Marine Pollutant
Transportation Class: 8 (9)
Precautions: Corrosive, Other Hazard
Packing Group: II
Environment Hazard: Yes
Required Labels: 8
ERG Code (IATA): 8L
EmS (IMDG): F-A, S-B

Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):
 Nonyl Phenol (CAS 84852-15-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET

CERCLA Hazardous Substance List (40 CFR 302.4):

Bisphenol-A (CAS 80-05-7)	LISTED
Phenol (CAS 108-95-2)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No

SARA 311/312 Hazardous chemical: Yes

SARA 313 (TRI reporting):

Component	CAS	% In Blend (approx.)
Bisphenol A	80-05-7	1-10
Nonyl Phenol	84852-15-3	1-5

US. California Proposition 65:

WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to www.P65Warnings.ca.gov.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	40-60	1	KNOWN	A2	CA65 (Carcinogenic)
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected CA65 - California Prop 65					

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
Japan	One or more components in this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL)
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

RPS-752 Epoxy Bonding Agent

SAFETY DATA SHEET



16. Other Information

Date Prepared or Revised: December 2021
Supersedes: May 2020
Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
CPR:	Controlled Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H-Phrases Under Section 3

H315:	Causes skin irritation.
H319:	Causes serious eye irritation.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H350:	May cause cancer.
H373:	May cause damage to organs through prolonged or repeated exposure.
H411:	Toxic to aquatic life with long lasting effects.

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2021 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

A Component 752: XCOM3B	B Component 752: XCOM3B XCORR
----------------------------	-------------------------------------