



PARA-STIK® INSULATION ADHESIVE

Commercial Product Data Sheet

Para-Stik Insulation Adhesive is a single-component, moisture-cure, solvent-free, low-rise foam polyurethane rigid insulation adhesive. Para-Stik Insulation Adhesive is used to adhere approved rigid insulation panels to substrates approved in advance by Siplast.

Contact Siplast for information on approved product uses.

USES:
RIGID INSULATION ADHESIVE

PRODUCT INFORMATION

Shelf Life	15 months
Temperature Limitations	<p>Recommended Temperature of Product at Point of Application: 75°F (24°C)</p> <p>Ambient and Substrate Temperatures at Time and Point of Application: Minimum 33°F (1°C)</p>

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

Para-Stik Insulation Adhesive should be stored in a cool, dry location at temperatures between 45°F (7°C) and 75°F (24°C). Store materials out of direct exposure to the elements.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Weight of Full Tank Unit: 30 lb (14 kg);
23 lb (10 kg) Net Chemical Weight

Tanks Per Pallet: 40

Hose/Wand Kit:
Brass Ball Valve
4 ft (1 m) Flexible Hose
28 in (712 mm) PVC Dispensing Wand
Para-Stik Hose/Wand Kits Are Sold Separately

Listings, Approvals, & Certifications

