

# ORANGE PEEL

Citrus Cleaner

Citrus-based solvent degreaser/stripper



## DESCRIPTION

**ORANGE PEEL** concentrate is a cost effective, natural citrus solvent, cleaner and degreaser. **ORANGE PEEL** is an innovative solution for the toughest industrial applications. **ORANGE PEEL** will effectively remove grease, grime and other contaminants from architectural concrete and other surfaces.

**ORANGE PEEL** can also be used to remove asphalt from tools or paving machines and dissolve/strip many types of carpet and tile cutback adhesives safely and effectively. Standard harsh cleaners and degreasers are made from chlorinated solvents or hydrocarbon solvents that can be hazardous to use and to dispose.

**ORANGE PEEL** is VOC compliant with a pleasant citrus odor. (check local regulations)

## APPLICATION

**Storage:** Store material in the original tightly closed containers. Do not allow the accumulation of water, dirt or other contaminants.

**Coverage:** Concentrated **ORANGE PEEL** is ready-to-use on tough jobs or follow the recommended dilution table. Field test to determine the optimal concentration for the specific application. The product will turn white when diluted with water.

<i>Application</i>	<i>Recommended Dilution</i>
Heavy Stains, Tire Marks, Cures Cutback Adhesives, Asphalt Paving Equipment	No Dilution
Industrial Dirt/Grime/residual tilt-up bondbreaker	1 part to 4 parts water
Industrial/Institutional Warehouse Floor, General Cleaning	1 part to 5 parts water

**Use:** Scrape off excess accumulations of grease, grime and contaminants. Apply **ORANGE PEEL** to the floor or stain either as a concentrate or at the recommended dilution rate. Spread uniformly over the surface and allow product to penetrate for approximately 5 minutes. **ORANGE PEEL**'s unique blend of emulsifiers and wetting agents allow maximum penetration for effective cleaning.

Scrub area with a stiff bristle broom or a power floor scrubber. Thoroughly rinse the entire area with clean water. Stubborn stains may require additional treatments.

Stripping acrylic curing/sealing and resin curing compounds will require an undiluted application, keeping the material wet with itself for 20-30 min. Then apply water while scrubbing and vacuuming up the residue. Heavy build up may require additional treatments to completely remove.

## PACKAGING

**ORANGE PEEL** is available in:  
55 gallon drums / 208 Liter  
5 gallon pails / 18.9 Liter  
1 gallon jugs (4 to case) / 3.78 Liter

## STANDARDS

**ORANGE PEEL** is a VOC compliant, non-etching cleaner/degreaser/stripper.

## SHELF LIFE

Shelf life of **ORANGE PEEL** in the original tightly closed containers is three years from date of manufacture.

## LIMITATIONS

Check local VOC regulations before using.

**Not VOC compliant in CA. Use SpecChem "Berry Clean" in CA.** Conduct tests prior to application on various painted surfaces. **ORANGE PEEL** may soften, discolor and/or remove some paints. Do not use on resilient tile, rubber, or asphalt. **ORANGE PEEL** is highly concentrated, personal protective equipment should be worn.

**DO NOT EXPOSE TO OR APPLY NEAR FIRE OR FLAMES. FOR WELL VENTILATED OR EXTERIOR USE ONLY!**

## PRECAUTIONS

**DO NOT CUT OR WELD CONTAINER  
KEEP AWAY FROM OPEN FLAME  
INDUSTRIAL USE ONLY  
USE PROTECTIVE GLOVES AND GOGGLES  
HARMFUL IF SWALLOWED**

Additional precautions, safety and first aid information are contained in the Safety Data Sheet

## TECHNICAL SERVICES

For assistance, contact technical services at:  
866-791-8700 913-371-8700  
www.specchemllc.com

**24 HOUR EMERGENCY CONTACT:**

VelocityEHS  
1-(800)255-3924 (North America) +1-813-248-0585  
(International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India)  
800-099-0731 (Mexico)  
Made in America

## WARRANTY

**NOTICE-READ CAREFULLY  
CONDITIONS OF SALE**

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

**WARRANTY LIMITATION**

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. **NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.**

**INHERIT RISK**

Purchaser assumes all risk associated with the use or application of the product.

**SPEC CHEM**  
Solution to Service

1511 Baltimore Ave, Suite 600  
Kansas City, MO 64108  
www.specchem.com 866.791.8700