



DRAGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: MAY 28, 2024

1. PRODUCT NAME

DRAGOTACK TAPE

2. MANUFACTURER

Stego Industries, LLC
 216 Avenida Fabricante, Suite 101
 San Clemente, CA 92672
 Sales, Technical Assistance
 Ph: (877) 464-7834
 contact@stegoindustries.com
stegoindustries.com



3. PRODUCT DESCRIPTION

USES: Dragotack Tape is a solvent-resistant, double-sided adhesive strip used to bond and seal Drago® Wrap to concrete, masonry, wood, metal, and other surfaces. Dragotack Tape is a flexible and moldable material to allow for a variety of applications and installations.

COMPOSITION: Dragotack Tape is made from a solvent-resistant blend of synthetic rubber and resins.

SIZE: Dragotack Tape is 2" x 50'. Dragotack Tape ships 12 rolls in a case.

4. TECHNICAL DATA

TABLE 4.1: PHYSICAL PROPERTIES OF DRAGOTACK TAPE

PROPERTY	TEST	RESULTS
Dimensions		2" x 50'
Total Thickness		30 mil
Color		Grey
Material		Synthetic rubber blend
Permeance	ASTM F1249	0.03 perms (30 mil)
Adhesion to Steel	ASTM D1000	12.5 lbs/in width
Chemical Resistance (TCE, PCE, Toluene, Xylene)	ASTM D471 / D543	No significant change to mass or volume.
Installation Temperature		40°F / 110°
In Service Temperature Range		-20°F / +140°F
VOC Content		No VOCs, 100% solids

Note: perm unit = grains/(ft²*hr*in-Hg)

DRAGOTACK TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: MAY 28, 2024

5. INSTALLATION

TO WALLS AND FOOTINGS: Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply Drago Wrap, remove the exposed release liner and press Drago Wrap firmly against DragoTack Tape to secure.

Cut DragoTack Tape using a utility knife or scissors. Cut DragoTack Tape before removing the release liner for easier cutting. Install DragoTack Tape between 40°F and 110°F.

Review Drago Wrap's complete installation instructions prior to installation.

6. AVAILABILITY & COST

DragoTack Tape is available nationally through our network of building supply distributors. For current cost information, contact your local Drago distributor or Stego® Sales Representative.

7. WARRANTY

Stego believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego does not guarantee results from the use of the information provided herein. Stego does offer a limited warranty on Drago Wrap. Please see stegoindustries.com/legal

8. MAINTENANCE

Store DragoTack Tape in a dry and temperate area.

9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego or by visiting the website.

Email: contact@stegoindustries.com

Contact Number: (877) 464-7834

Website: stegoindustries.com

10. FILING SYSTEMS: stegoindustries.com

