



# PANGO CLAW® (3" WIDE)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR BARRIER 31 31 16, 07 26 00, 03 30 00 | VERSION: JUN 12, 2024

## 1. PRODUCT NAME

**PANGO CLAW (3" WIDE)**

## 2. MANUFACTURER

Stego Industries, LLC  
 216 Avenida Fabricante, Suite 101  
 San Clemente, CA 92672  
 Sales, Technical Assistance  
 Ph: (877) 464-7834  
 contact@stegoindustries.com  
 stegoindustries.com



## 3. PRODUCT DESCRIPTION

**USES:** Pango Claw is a multi-layered tape that is used to seal Pango® Wrap along its terminating edges (interior and perimeter) to the slab while the concrete is placed. Pango Claw allows wet concrete to cast into the textured top surface to form a mechanical bond/seal.

**COMPOSITION:** Pango Claw is composed of polyethylene film, aperture film, and an acrylic, pressure-sensitive adhesive.

**SIZE:** 3" X 180'

**FEATURES AND BENEFITS:** Pango Claw (3" Wide) ships 16 rolls in a case | Independent, university efficacy testing establishing termite barrier efficacy | Low water vapor permeance | Exceptional adhesion to Pango Wrap | Outstanding bond seal to concrete | Made in the USA

## 4. TECHNICAL DATA

**TABLE 1: PHYSICAL PROPERTIES OF PANGO CLAW (3" WIDE)**

PROPERTY	TEST METHOD	RESULTS
Total Thickness		26 mil
Permeance	ASTM F1249 – Test Method for Water Vapor Transmission Rate Through Plastic Film and Sheeting Using a Modulated Infrared Sensor	0.074 perms
180° Adhesion Peel Strength	ASTM D903	10.0 lbf/in.
Shear Adhesion Strength	1 in <sup>2</sup> shear test using an Instron 3345 Machine	31 lbf/in <sup>2</sup>
Dimensions		3" x 180'

Note: perm unit = grains/(ft<sup>2</sup>\*hr\*in-Hg)

## 5. INSTALLATION

**UNDER SLAB & CRAWL SPACE:** Clean surface of Pango Wrap to ensure that it is free of moisture, frost, dirt, and debris prior to the installation of Pango Claw. When ready to apply Pango Claw, peel back the release liner and apply to Pango Wrap. Pango Claw should be completely on Pango Wrap.

To detail, cut Pango Claw with a box knife or scissors. Pango Claw should be installed above 40°F for maximum adhesion.

**TIP:** Wrap the release liner back over the entire roll while unrolling Pango Claw. This technique will allow the release liner to pull off easily and keep it out of the way.

Review Pango Wrap's complete installation instructions prior to installation.

Continued...

Note – legal notice on page 2.

## PANGO CLAW® (3" WIDE)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR BARRIER 31 31 16, 07 26 00, 03 30 00 | VERSION: JUN 12, 2024

### 6. AVAILABILITY & COST

For cost and availability of Pango Claw, please contact your local Stego® Sales Representative.

### 7. WARRANTY

Stego believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego does not guarantee results from the use of the information provided herein. Stego offers a limited warranty on Pango Claw. Please see [stegoindustries.com/legal](https://stegoindustries.com/legal)

### 8. MAINTENANCE

Store Pango Claw in a dry and temperate area.

### 9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, testing information, and additional information can be obtained by contacting Stego or by visiting the website.

**Email:** [contact@stegoindustries.com](mailto:contact@stegoindustries.com)  
**Contact Number:** (877) 464-7834  
**Website:** [stegoindustries.com](https://stegoindustries.com)

### 10. FILING SYSTEMS: [stegoindustries.com](https://stegoindustries.com)

