

WATERPROOFING

FLUID-APPLIED

SHEET-APPLIED

	TREMproof 2306C	TREMproof 2011/60	TREMproof 260	TREMproof 6100	TREMproof PUMA
VERTICAL					
Backfilled Wall (<20')	•	•	•		
Backfilled Wall (>20')	•	•	•		
Blindside/Lagging Wall (<20')			•		
Blindside/Lagging Wall (>20')			•		
HORIZONTAL					
Split Slab or Paver	•	•		•	•
Below Slab on Grade					
Vegetated Roofs	•			•	•
Planters	•			•	•
OTHER					
Methane Barrier**			•		
Submerged Conditions**	•			•	
Green/Damp Concrete	•		•		
Nudura® Insulated Concrete Forms (ICF)			•		

	Paraseal GM	Paraseal	Paraseal GM/LG 60mil	Paraseal LG	TREMproof Amphibia	Paraseal GM/LG 20mil	TREMproof 560A
VERTICAL							
Backfilled Wall (<20')	•	•					•
Backfilled Wall (>20')	•	•					•
Blindside/Lagging Wall (<20')		•		•	•		
Blindside/Lagging Wall (>20')		•		•	•		
HORIZONTAL							
Split Slab or Paver							
Below Slab on Grade		•		•	•		
Vegetated Roofs							
Planters							
OTHER							
Methane Barrier**			•	•			
Submerged Conditions**				•	•	•	
Green/Damp Concrete	•	•	•	•	•		•
Nudura® Insulated Concrete Forms (ICF)							•

* The Commercial Waterproofing Selection Guide is to be used as a general reference and reflects components that become integrated into a complete waterproofing system. Please consult your Tremco Rep for recommendations based on your local practices and warranty requirements.
 ** Please consult your Tremco Rep for recommendations and approval of your specific application.
 Reference the current product data sheet on our website at tremcosealants.com for more specific product information. For priming recommendations, contact Tremco Technical Services or our Primer Guide.

Tremco | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.

Part of

 Construction Products Group

DRAINAGE

RESIDENTIAL DRAINAGE

VERTICAL APPLICATIONS	Backfilled Walls < 16'	Insulated Concrete Forms (ICF)	Compressive Strength	In-Plane Flow Rate	Thickness	Roll Dimensions
Drainstar 5X	•	•	6,700 psf (320 kPa)	10 gpm/ft (277 Lpm/m)	.313 in (8 mm)	6.6' x 50'
Drainstar Wall Drain 90	•	•	9,000 psf (431 kPa)	12.5 gmp/ft (155 Lpm/m)	.25 in (6.35 mm)	4' x 50'
Drainstar Wall Drain 720	•	•	5,200 psf (249 kPa)	12.5 gmp/ft (155 Lpm/m)	.315 in (8 mm)	6' x 65.5'
Drainstar Wall Drain 960	•	•	5,200 psf (249 kPa)	12.5 gmp/ft (155 Lpm/m)	.315 in (8 mm)	8' x 65.6'

COMMERCIAL DRAINAGE

BLINDSIDE WALL (VERTICAL)	Blindside / Lagging Walls < 20'	Blindside/ Lagging Walls > 20'	Insulated Concrete Forms (ICF)	Compressive Strength	In-Plane Flow Rate	Thickness	Roll Dimensions
TREMDrain NW	•			11,000 psf (527 kPa)	12.5 gpm/ft (155 Lpm/m)	.25 in (6.35 mm)	4' x 50'
TREMDrain 100NW		•		15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain 1000PF		•		15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain 6000X		•		15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.4 in (10 mm)	6' x 50'
TREMDrain 6000NW		•		15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.4 in (10 mm)	6' x 50'
TREMDrain Total Drain		•		9,500 psf (455 kPa)	21 gpm/ft (261 Lpm/m)	.44 to 1 in (11 to 25.4 mm)	2' x 50'

BACKFILLED WALL (VERTICAL)

TREMDrain NW	•		•	11,000 psf (527 kPa)	12.5 gpm/ft (155 Lpm/m)	.25 in (6.35 mm)	4' x 50'
TREMDrain QSP	•	•	•	10,800 psf (517 kPa)	18 gpm/ft (224 Lpm/m)	.25 in (6.35 mm)	4' x 4'
TREMDrain 1000NW		•	•	15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain 1000PF		•	•	15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain Total Drain	•	•	•	9,500 psf (455 kPa)	21 gpm/ft (261 Lpm/m)	.44 to 1 in (11 to 25.4 mm)	2' x 50'

HORIZONTAL APPLICATIONS

	Split Slab	Below Pavers	Below Slab On-Grade	Vegetated Roofs	Planters	Compressive Strength	In-Plane Flow Rate	Thickness	Roll Dimensions
TREMDrain S NW	•	•	•			30,000 psf (1436 kPa)	13 gpm/ft (161 Lpm/m)	.25 in (6.35 mm)	4' x 50'
TREMDrain 1000PF	•	•				15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain GS 1/2"				•	•	15,000 lb/ft (73,236 kPa)	6 gpm/ft (68 Lpm/m)	.44 in (11 mm)	4' x 50'
TREMDrain GS 1"				•	•	9,000 lb/ft (43,941 kPa)	21 gpm/ft (261 Lpm/m)	.4 in (10 mm)	6' x 50'
TREMDrain 2000NW	•	•			•	18,000 psf (862 kPa)	18 gpm/ft (224 Lpm/m)	.4 in (10 mm)	6' x 50'
TREMDrain 3000NW	•	•				30,000 psf (1436 kPa)	13 gpm/ft (161 Lpm/m)	.44 to 1 in (11 to 25.4 mm)	2' x 50'
TREMDrain 6000NW	•	•				15,000 psf (718 kPa)	18 gpm/ft (224 Lpm/m)	.4 in (10 mm)	6' x 50'