TREMPROOF[®] DWS

Dual Waterproofing System (DWS) Comprised of TRA Sheeting Embedded into TREMproof 250GC

System Overview

TREMproof[®] DWS is a dual membrane waterproofing system comprised of TREMproof TRA sheeting embedded into TREMproof 250GC. This unique waterproofing system is designed to have tenacious adhesion, long term durability, and remarkable chemical stability. The elastomeric properties of the system's components enable the complete assembly to withstand the most demanding conditions.

Typical applications for TREMproof DWS include:

- Backfilled Walls Terraces
- Split Slab
- Plaza Decks
- Planters
- Under Paver Systems
- Features & Benefits
- Dual-layer system is designed to withstand the most rigorous waterproofing applications
- Waterproofs plaza decks, terraces, backfilled walls, planters, split slab applications, and can be used anywhere the ultimate waterproofing is required
- Can be applied in as little as 24 hours after the removal of concrete forms
- Can be applied to damp concrete, reducing the delays associated with rain or other sources of moisture
- Cold-applied application minimizes the need for specialized equipment
- Low Volatile Organic Compounds (VOCs)
- Proven, durable performance



Components

1 TREMproof 250GC Vulkem[®] 191 QD 2 3 **TREMproof 250GC** 4 TRA Sheeting 5 TREMDrain[™] Drainage 6 Insulation 7 Overburden

5

4

