

SAFETY DATA SHEET

1. Identification

Material name: TREMPRO 644 RTV ALUMINUM 3
Material: 6445105 312

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Dermal)	Category 4
Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	76.68 %
Acute toxicity, dermal	80.03 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	92.25 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	86.68 %
Chronic hazards to the aquatic environment	86.68 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Harmful in contact with skin or if inhaled.
May cause cancer.
Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

Response: IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. Call a POISON CENTER or doctor/ physician if you feel unwell. Specific measures (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Distillates, petroleum, hydrotreated middle	64742-46-7	5 - <10%
Silicon dioxide, amorphous	112945-52-5	5 - <10%
Ethyltriacetoxysilane	17689-77-9	1 - <5%
Acetic acid	64-19-7	1 - <3%
Barium sulfate	7727-43-7	0.1 - <1%

Aluminum	7429-90-5	0.1 - <1%
Titanium dioxide	1317-80-2	0.1 - <1%
Octhilionone	26530-20-1	0.01 - <0.1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Call a POISON CENTER/doctor if you feel unwell.
Eye contact:	Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Personal Protection for First-aid Responders:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.
-------------------	--------------------------

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.
--	---

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):	Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.
Safe handling advice:	Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required.
Contact avoidance measures:	No data available.
Hygiene measures:	Avoid contact with skin. Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

Storage

Safe storage conditions:	Store locked up.
Safe packaging materials:	No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates, petroleum, hydrotreated middle - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2014)
Distillates, petroleum, hydrotreated middle - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon dioxide, amorphous	TWA	20 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as

		particles per cubic foot of air	amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Acetic acid	TWA	10 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	STEL	15 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	10 ppm 25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Aluminum - Total dust. - as Al	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum - Respirable fraction. - as Al	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Aluminum - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Titanium dioxide - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Titanium dioxide - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)

Titanium dioxide - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)

Chemical name	Type	Exposure Limit Values	Source
Distillates, petroleum, hydrotreated middle - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Distillates, petroleum, hydrotreated middle - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Distillates, petroleum, hydrotreated middle - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)

Chemical name	Type	Exposure Limit Values	Source
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Amorphous silica - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Amorphous silica - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Distillates, petroleum, hydrotreated middle - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Distillates, petroleum, hydrotreated middle - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Distillates, petroleum, hydrotreated middle - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Acetic acid	STEL	15 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Acetic acid	STEL	15 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	10 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)

Acetic acid	TWA	10 ppm	25 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	15 ppm	37 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	10 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Barium sulfate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Barium sulfate - Inhalable	TWA		5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Barium sulfate - Total dust.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Aluminum - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - as Al	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - Welding fume. - as Al	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - Respirable.	TWA		1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Titanium dioxide - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Titanium dioxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Titanium dioxide - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Avoid contact with skin. Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

- Physical state:** solid
- Form:** Paste
- Color:** Gray
- Odor:** Pungent
- Odor threshold:** No data available.
- pH:** No data available.
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.
- Flash Point:** No data available.
- Evaporation rate:** Slower than Ether
- Flammability (solid, gas):** No
- Upper/lower limit on flammability or explosive limits**
 - Flammability limit - upper (%):** No data available.
 - Flammability limit - lower (%):** No data available.

Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.01
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	ATEmix: 10,068.82 mg/kg
Dermal	
Product:	ATEmix: 1,877.92 mg/kg
Inhalation	
Product:	ATEmix: 1.78 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Distillates, petroleum, hydrotreated middle	in vivo (Rabbit): Irritating , 24 - 72 h
Ethyltriacetoxysilane	in vivo (Rabbit): Category 1B , 24 - 72 h
Acetic acid	in vivo (Rabbit): Slightly irritating , 72 h
Barium sulfate	validated "in vitro" test method Not irritant
Aluminum	in vivo (Rabbit): Not irritant , 24 - 72 h
Titanium dioxide	in vivo (Rabbit): Not irritant , 1 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Distillates, petroleum, hydrotreated middle	Rabbit, 24 hrs: Not irritating
Ethyltriacetoxysilane	Rabbit, 24 - 72 hrs: Not irritating
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating
Aluminum	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Distillates,
petroleum,
hydrotreated
middle Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall
evaluation: Carcinogenic to humans.

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Distillates,
petroleum,
hydrotreated
middle Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Distillates, petroleum, hydrotreated middle	LL 50 (Oncorhynchus mykiss, 96 h): 1.13 mg/l QSAR QSAR, Key study
Ethyltriacetoxysilane	LC 50 (Danio rerio, 96 h): 251 mg/l Experimental result, Key study
Acetic acid	LC 50 (Oncorhynchus mykiss, 96 h): > 1,000 mg/l Experimental result, Key study
Barium sulfate	LC 50 (Danio rerio, 96 h): > 3.5 mg/l Experimental result, Key study
Aluminum	LC 50 (Pimephales promelas, 96 h): 20.3 mg/l Experimental result, Weight of Evidence study
Titanium dioxide	LC 50 (Pimephales promelas, 96 h): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study EC 10 (Carassius auratus, 24 h): 10 mg/l Experimental result, Not specified
Octhilione	LC 50 (Oncorhynchus mykiss, 96 h): 0.047 mg/l

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Distillates, petroleum, hydrotreated middle	EC 50 (Daphnia magna, 48 h): 7.385 mg/l QSAR QSAR, Key study
Ethyltriacetoxysilane	EC 50 (Daphnia magna, 48 h): 65 mg/l Experimental result, Weight of Evidence study
Acetic acid	EC 50 (Daphnia magna, 48 h): 65,000 µg/l EC 50 (Daphnia magna, 48 h): > 1,000 mg/l Experimental result, Key study
Barium sulfate	LC 50 (Daphnia magna, 48 h): 14,500 µg/l Experimental result, Key study
Aluminum	LC 50 (Ceriodaphnia dubia, 48 h): 0.72 mg/l Experimental result, Weight of Evidence study
Titanium dioxide	EC 50 (Daphnia magna, 48 h): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
-----------------	--------------------

Specified substance(s):

Distillates, petroleum, hydrotreated middle

NOAEL (Oncorhynchus mykiss): 0.069 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product:

No data available.

Specified substance(s):

Distillates, petroleum, hydrotreated middle

NOAEL (Daphnia magna): 0.163 mg/l QSAR QSAR, Key study

Ethyltriacetoxysilane

NOAEL (Daphnia magna): >= 100 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Acetic acid

NOAEL (Daphnia magna): 22.7 mg/l Experimental result, Not specified

Aluminum

NOAEL (Ceriodaphnia dubia): 1.1 mg/l Experimental result, Weight of Evidence study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.

Specified substance(s):

Distillates, petroleum, hydrotreated middle

41.96 % Detected in water. Experimental result, Key study

Ethyltriacetoxysilane

79.5 % (28 d) Detected in water. Experimental result, Key study
79.5 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Key study

Acetic acid

96 % (20 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product:

No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:

No data available.

Specified substance(s):

Acetic acid

Various, Aquatic sediment QSAR, Key study

Aluminum

Brook trout (Salvelinus fontinalis), Bioconcentration Factor (BCF): 36 (Flow through)

Octhillionone

Bluegill (Lepomis macrochirus), Bioconcentration Factor (BCF): 165 (Flow through)

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Acetic acid Log Kow: -0.17

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Acetic acid	5000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Acute toxicity (any route or exposure)
- Carcinogenicity

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

- Proprietary ingredients in Wacker Elastosil 5103P series (Codes 28939, 28940, 28961, 28962, 28963, 28964, 28965)
- Amorphous silica
- Distillates, petroleum, hydrotreated middle
- Silicon dioxide, amorphous
- Ethyltriacetoxysilane
- Acetic acid
- Barium sulfate
- Aluminum
- Titanium dioxide
- Octhilione

US. Massachusetts RTK - Substance List

Chemical Identity

Amorphous silica
Distillates, petroleum, hydrotreated middle
Silicon dioxide, amorphous
Acetic acid

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Amorphous silica
Distillates, petroleum, hydrotreated middle
Silicon dioxide, amorphous
Acetic acid

US. Rhode Island RTK

Chemical Identity

Amorphous silica
Distillates, petroleum, hydrotreated middle
Acetic acid

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 21 g/l

VOC Method 310 : 2.03 %

Inventory Status:

EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Australia Industrial Chem. Act (AIIC):	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this

product are not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals: One or more components in this product are not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are not listed on or exempt from the Inventory.

Switzerland New Subs Notified/Registered: One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 01/27/2022

Version #: 1.4

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.