



TECHNICAL DATA SHEET

TREMCO® PUMA PRIMER

Methyl-Methacrylate (MMA) Primer

PRODUCT DESCRIPTION

Tremco PUMA Primer is a methyl-methacrylate (MMA), two-component primer for porous and non-porous substrates. It is used in Tremco's polyurethane methacrylate (PUMA) technology systems. Tremco PUMA Primer must be used with Tremco PUMA Initiator+.

BASIC USES

Tremco PUMA Primer is used on concrete, metal and wood surfaces before a Tremco PUMA base coat is applied.

AVAILABILITY

Immediately available from your local Tremco Sales Representative.

PACKAGING

Tremco PUMA Primer: 6-gal pails

INSTALLATION

Concrete shall be water-cured and attain a 3000 PSI minimum compressive strength for waterproofing and pedestrian traffic, 4000 PSI for vehicular traffic. Concrete finish shall be a light steel trowel followed by an equivalent ICRI #3-#4 finish. Moisture content in the concrete must be less than 6% as measured using a Tramex CME 4 Moisture Meter. Depending on concrete construction and job site location, additional concrete testing may be required. Please contact your local Tremco representative.

Tremco PUMA components are designed for use with the Vulkem® EWS and TREMproof® PUMA systems. Please refer to the appropriate application instructions for complete application details. The techniques involved may require modification due to job-site specific conditions. Consult your Tremco representative for recommended site conditions and requirements.

LIMITATIONS

- Do not apply to damp or contaminated surfaces.
- Use with adequate ventilation.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
% Solids (by weight)	ASTM D1353	100%
Drying Time @ 75 °F, 50% RH	ASTM D1640	17 mil film, 1 hr
Cure Time		3 min

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

EWSP-DS/0923

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com