



# SEALANT SELECTION GUIDE

	Vulkem 116	Vulkem 445SL	Dymonic 100	Vulkem 445SL	Dymonic FC	Spectrem 1	Spectrem 2	Spectrem 3	Spectrem 4-TS	Spectrem 800	Spectrem 900SL	Tremsil 2000	Tremsil 600	Proglaze SSG	Proglaze	Tremflex 834	Acoustical Sealant	TREMPRO 830+	Willseal 600**
<b>Chemistry</b>	U	U	U	U	H	S	S	S	S	S	S	S	S	S	A	B	T	PT	
<b>Non-Sag or Pourable</b>	NS	P	NS	P	NS	NS	NS	NS	NS	NS	P	NS	NS	NS	NS	NS	NS	NS	0
<b>Single- or Multi-Component</b>	S	S	S	M	S	S	S	M	S	S	S	S	S	S	S	S	S	S	0
<b>SWRI</b>		Yes			Yes	Yes													
<b>GREENGUARD Gold</b>		Yes		Yes	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes				Yes
<b>Movement Capability</b>	± 25%	+100/-50%*	+100/-50%*	+100/-50%*	± 35%	+100/-50%	± 50%	± 50%*	± 50%*	+100/-50%	+100/-50%	± 25%	± 25%	± 25%	± 25%	± 12.5%		± 25%	
<b>MASONRY</b>																			
Poured Concrete	●	●	●	●	●	●	●	●	●	●	●							●	●
Cast-in-Place/Tilt-Up	●		●		●	●	●	●	●	●	●							●	●
CMU Block	●		●		●	●	●	●	●	●								●	●
Brick	●	●	●	●	●	●	●	●	●	●								●	●
Natural Stone	●	●	●	●	●	●	●	●	●									●	●
Stucco	●		●		●	●	●	●	●									●	●
Reservoir†	●		●																
<b>METALS</b>																			
Curtain Walls			●		●	●	●	●	●				●	●				●	●
Flashing	●		●		●	●	●						●					●	●
Sidings	●		●		●	●	●						●			●		●	●
Window and Door Perimeters	●		●		●	●	●	●	●				●	●		●		●	●
<b>DRYVIT®/EIF SYSTEMS</b>					●	●		●	●										●
<b>VINYL AND PLASTICS</b>	●		●		●	●							●			●		●	●

## Legend

### Chemistry

- U = Urethane
- H = Hybrid
- S = Silicone
- A = Acrylic
- B = Butyl
- T = Thermoplastic
- PT = Pre-Compressed Tape

### Non-Sag or Pourable

- NS = Non-Sag
- P = Pourable
- O = Other

### Single- or Multi-Component

- S = Single-Component
- M = Multi-Component
- O = Other

The Sealant Selection Guide should only be used as a guide. Reference the Data Sheet for more specific information and/or consult your local Tremco Representative or Technical Services.

\* Modified ASTM C719

\*\* Willseal 600 can be used in non-immersed applications where there is no ponding water and as a backer rod on horizontal joints.

† For use in non-treated, non-potable water.

For priming recommendations, please contact Tremco Technical Services or reference the Primer Guide on our web site.

	Vulkem 116	Vulkem 45SSL	Dymonic 100	Vulkem 445SSL	Dymonic FC	Spectrem 1	Spectrem 2	Spectrem 3	Spectrem 4-TS	Spectrem 800	Spectrem 900SL	Tremsil 200	Tremsil 600	Proglaze SSG	Proglaze	Tremflex 834	Acoustical Sealant	TREMPRO 830+	Willseal 600**	
<b>Chemistry</b>	U	U	U	U	H	S	S	S	S	S	S	S	S	S	S	A	B	T	PT	
<b>Non-Sag or Pourable</b>	NS	P	NS	P	NS	NS	NS	NS	NS	NS	P	NS	NS	NS	NS	NS	NS	NS	0	
<b>Single- or Multi-Component</b>	S	S	S	M	S	S	S	S	M	S	S	S	S	S	S	S	S	S	0	
<b>SWRI</b>	Yes		Yes		Yes		Yes		Yes		Yes		Yes		Yes		Yes		Yes	
<b>GREENGUARD Gold</b>		Yes		Yes	Yes	Yes	Yes	Yes			Yes	Yes	Yes	Yes	Yes				Yes	
<b>Movement Capability</b>	± 25%	+100/-50%*	+100/-50%*	+100/-50%*	± 35%	+100/-50%	± 50%	± 50%*	± 50%*	+100/-50%	+100/-50%	± 25%	± 25%	± 25%	± 25%	± 12.5%		± 25%		
<b>GREEN AND DAMP CONCRETE</b>		●	●	●															●	
<b>GLASS</b>						●	●					●	●	●	●				●	
<b>WOOD</b>	●	●	●	●	●	●	●	●	●							●	●	●	●	
<b>DRYWALL (GYPSUM)/METAL STUD PARTITION</b>																●	●		●	
<b>GENERAL GLAZING</b>																				
Toe Bead						●	●							●	●					
Heel Bead						●	●							●	●					
Cap Bead						●	●	●	●					●	●	●			●	
Weather Seal	●		●		●	●	●	●	●					●						
Bedding					●		●							●		●	●		●	
<b>STRUCTURAL GLAZING</b>																				
Tensile Bead 2-Sided							●								●					
Tensile Bead 4-Sided															●					
<b>PROTECTIVE GLAZING</b>																				
Hurricane/Impact															●					
Bomb Blast															●					
Tub and Tile/Sanitary												●								
Jet Fuel Resistance	●	●	●	●							●									

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building



Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.  
© Tremco CPG Inc. 2024