



# CONSTRUCTION SEALANTS COLOR CARD

## PROGLAZE®

Proglaze is a one-part, moisture curing, acetoxy silicone sealant. Proglaze provides a high-performance seal for a wide variety of glazing applications such as cap beads and metal-to-metal joints. Additional uses include a variety of in-plant applications.



WHITE  
300C



ALUMINUM  
300C



BLACK  
300C



CLEAR  
300C

---

## TREMSIL® 200

Tremsil 200 is a one-part, acetoxy silicone sealant that produces a weather-tight seal to glass, metal, porcelain, ceramic, and most painted surfaces. White contains a fungicide, making it suitable for use in bathrooms. Clear is supplied with an integral fungicide.



WHITE  
300C



CLEAR  
300C



ALUMINUM  
300C



BLACK  
300C

---

## TREMSIL® 600

Tremsil 600 is a one-part, neutral cure, fast skinning, medium modulus silicone sealant. Tremsil 600 is ideal for use as an in-plant glazing sealant for applications that includes back bedding, cap, heel and toe beads and sash joinery. It can also be used in a variety of commercial construction applications.



WHITE  
300C/600S/5P\*/55D



ANODIZED ALUMINUM  
300C/600S



BLACK  
300C/600S\*/5P/55D



CLEAR  
300C/600S/5P\*/55D\*

---

## BUTYL SEALANT

Tremco Butyl Sealant is a one-part sealant for use in a variety of applications, such as corrugated sheet lap joints, curtainwall applications, bedding thresholds, secondary seals in glazing and where a seal is required against Tremco neoprene or EPDM gaskets.



WHITE  
300C



ALUMINUM STONE  
300C



BLACK  
300C

## TREMFLEX® 834

Tremflex 834 is a pure acrylic sealant used for general purpose interior and exterior caulking and as a back-bedding glazing compound.



WHITE  
300C/600S/5P



LIMESTONE  
300C/5P



CLEAR  
300C

## VULKEM® 45SSL

Vulkem 45SSL is a semi-self-leveling, single-component, moisture-curing, low-modulus, polyurethane sealant formulated for use in expansion joints in sidewalks, swimming pool decks, plazas, floors and any other horizontal surfaces with slopes up to 6% (ex. 1' rise for every 16' run).



WHITE  
850C/2P/5P\*



LIMESTONE  
850C/2P/5P/55D\*



GRAY  
850C/2P/5P/55D\*



BUFF  
850C/2P\*



BLACK  
850C/5P\*

## PRODUCT OFFERING GUIDE

**300C** - 300 mL (10 fl. oz.)  
Cartridge

**600S** - 600 mL (20.3 fl. oz.)  
Sausage

**850C** - 850 mL (28.7 fl. oz.)  
Cartridge

**2P** - 2 Gallon (7.57 Liters) Pail

**5P** - 5 Gallon (18.9 Liters) Pail

**55D** - 55 Gallon (208 Liters)  
Drums

\* indicates a special color