

USG DONN® BRAND CE™ ACOUSTICAL SUSPENSION SYSTEM


USG Donn® Brand CE™
Acoustical Suspension System/
USG Clean Room™ Acoustical
Panels with ClimaPlus™
Performance-Class 100

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM




Flat White
050

PROFILE



USG Donn® Brand

EDGE DETAIL



Square Edge

FEATURES AND BENEFITS

- Grid system with factory-applied white, closed-cell foam gaskets for controlled-environments.
- Min. G30 hot-dipped galvanized body provides corrosion protection.
- Supports Clean Room HEPA filters and lights.
- ICC-ES evaluated for building code compliance and seismic installations (ICC-ESR-1222).
- Cleanability exceeds *FGI guidelines for healthcare facilities*.
- Capable of withstanding cleaning and/or disinfecting chemicals as tested in accordance with ASTM D5402.

APPLICATIONS

- Clean Rooms
- Hospitals
- Food processing areas
- Healthcare facilities, restricted and semirestricted areas
- Certified to meet ISO 14644-1 Class 5-8 (Fed. Standard 209E Class 100-100,000)

USG DONN® BRAND CE™ ACOUSTICAL SUSPENSION SYSTEM

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative


TECHNICAL SERVICES
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com


30 YEAR LIMITED SYSTEM WARRANTY
• No Visible Sag
• Mold/Mildew Protection

1-1/2" TEE SYSTEM®

Main Tee




Cross Tee 1-1/2"




15/16" TEE SYSTEM®



Main Tee



Cross Tee 1-1/2"



MOLDING^{5,6,7}



PHYSICAL DATA/ FOOTNOTES

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

AC3129/rev. 10-23
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

| ASTM Class | Length | Height | Item No. | Fire Rating | Color | Seismic Design Category ^{1,9} | | Rated Load ² | | |
|-------------------|------------|-----------------|----------------|------------------------------|------------|--|-------------------------------|-------------------------|-------------------|-------------------|
| | | | | | | IBC | ICC-ES Evaluated Installation | 4' Hanger Spacing | 5' Hanger Spacing | 6' Hanger Spacing |
| Heavy Duty | 12' | 1-1/2" 38 mm | DXWCE26 | Class A | Flat White | A-F | 7/8" Molding ACM7 Clip | 16 lb./LF | 8.5 lb./LF | 5 lb./LF |
| | 2' | 1-1/2" 38 mm | DXWCE224 | Class A | Flat White | | | | | |
| | 4' | 1-1/2" 38 mm | DXWCE424 | Class A | Flat White | | | | | |
| Intermediate Duty | 12' | 1.64" 42 mm | DXCE24 | Class A | Flat White | A-C | 7/8" Molding ACM7 Clip | 12 lb./LF | 6.1 lb./LF | 3.6 lb./LF |
| | Heavy Duty | 12' | 1.64" 42 mm | DXCE26 | Class A | Flat White | 7/8" Molding ACM7 Clip | 16 lb./LF | 7.3 lb./LF | 4.9 lb./LF |
| | 2' | 1-1/2" 38 mm | DXCE224 | Class A | Flat White | | | | | |
| | 4' | 1-1/2" 38 mm | DXCE424 | Class A | Flat White | | | | | |
| Wall Angle | Length | Item No. | Color | Hold-Down Clips ⁷ | | | | | | |
| | 12' | M7CE | Flat White | L15 | | | | | | |
| | 10' | US28CE | Flat White | C-8 | | | | | | |

Low Emissions (VOC)
CDPH 01350 v1.2-2017 compliance on select finishes, see usg.com for more details and documentation.

Product literature and samples

Data sheet: AC3129
DXCE™ sample: 207901

Material

Min. G30 hot-dipped galvanized steel body and cap. Baked-on polyester paint.

Installation

Must be installed in compliance with ASTM C636, ASTM E580, CISCA and standard industry practices, within all applicable code requirements. Class 5-8 (Fed. Standard 209E Class 100-100,000) installations require hold-down clips and US28CE molding. Install a L15 hold-down clip within 3 in. of each panel corner. For a 2' x 4' system install an additional L15 hold-down clip centered on the 4' side. Border panels shall have a C-8 hold-down clip within 3 in. of each panel corner. For a 2' x 4' system install an additional C-8 hold-down clip centered on the 4' side. Alternative assemblies and installation methods may be utilized when approved by the authority having jurisdiction.

Online tools

usgdesignstudio.com
cgcdesignstudio.com

Limitations

Interior applications only. The gasket face contains a protective strip that must be removed prior to panel installation. The standard gasket is not recommended for installations with metal panels. If metal panels are desired, a special gasket suitable for metal panels may be applied to the USG Donn® Brand CE™ Acoustical Suspension System through special order.

ICC Evaluation Service, LLC Report Compliance

For areas under ICC jurisdiction, see ICC-ES Evaluation Report ESR-1222 for allowable values and conditions of use. Reports are subject to reexamination, revision and possible cancellation. Refer to usg.com for most current version.

ASTM Load Compliance

Classified as Light, Intermediate or Heavy Duty when tested in accordance with ASTM C635.

Healthcare facilities^{3,4}

- No crevice created between suspension system and tile, meets or exceeds requirements for restricted and semirestricted areas.
- Capable of withstanding cleaning and/or disinfecting chemicals as tested in accordance with ASTM D5402-93.

Testing

Tested in accordance with Federal Standard 209E.

Notes

- All USG main tees, cross tees and main tee-hanger wire connections meet AC 368 and ASTM E580 requirements for tension and compression strength, as tested per ASTM E3090.
- Rated Load expressed in lb./LF based on simple span tests in accordance with ASTM E3090 with deflection limit of L/360. Duty rating is assigned based on rated load per ASTM C635.
- When required, lay-in light fixtures used in Clean Room ceiling assemblies shall be certified for Clean Room applications.
- HEPA filters must be supported at all four corners of grid module.
- For more information on moldings, see Perimeter Interface selector.
- Panels must be field-cut to size at the perimeter.
- US28CE molding and L15 and C-8 hold-down clips required for Clean Room ISO Class 5-8 (Fed. Standard 209E Class 100-100,000) applications.
- Metric sizes available by RTQ.
- Seismically tested in accordance with ASTM E3118.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CE, CLEAN ROOM, CLIMAPLUS, DONN, IT'S YOUR WORLD. BUILD IT, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

