USG Ceiling Solutions

# USG ENSEMBLE<sup>®</sup> ACOUSTICAL DRYWALL CEILING—CURVED SYSTEM

SEAMLESS, CURVED APPEARANCE WITH EXCELLENT ACOUSTIC PERFORMANCE



- Monolithic, curved appearance with fine finished in standard white and custom colors.
- System installed on factory pre-curved USG Drywall Main Tees.
- Perforated USG Sheetrock® Brand Panels, USG Ensemble® Four-Sided Taper™ Panels and acoustically transparent USG Ensemble™ Spray-Applied Finish opitimze sound performance NRC 0.80, CAC 40.
- Installs and finishes using traditional drywall techniques and USG Ensemble™ Spray-Applied finish.
- Up to 50% lower installed cost versus acoustical plaster systems.
- Backed by USG's advanced design and engineering, certified installer and sales support network, and full system warranty.

# APPLICATIONS

Lobbies

Concourses

• Atria

.

Performing arts spacesCorporate interiors

executive offices

• Board rooms/

- Classrooms/ higher education
  - Hospitality
  - Restaurants

# TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM

linkstai





CUSTOM COLORS AVAILABLE





USG Ensemble<sup>®</sup> Acoustical Drywall Ceiling - Curved System Thompson Savannah Hotel Architect: Smallwood, Reynolds, Steward & Associates Photo: ©Julie Soefer Photography

• Museums

USG ENSEMBLE<sup>®</sup> ACOUSTICAL DRYWALL CEILING-CURVED SYSTEM

**Backer Panel** 

1" USG Ensemble® High-NRC

**Declare** 

CUSTOM COLOR


**Base Panel** 


ORDER SAMPLES/LITERATURE **TECHNICAL SERVICES** USG: usg.com or samplit@usg.com 800 USG.4YOU (874-4968) CGC: contact Sales Representative TECHNICAL INFORMATION



**Fire Performance** 

Class A





NRC

0.80

CAC

40

LR

.85

### SYSTEM COMPONENTS

Products	Item Number	Sizes	Packaging	Quantity	Notes
USG Factory Curved Main Tees 20' minimum radius (vault) and 10' minimum radius (valley)	DGWXXXXX	10' 12'	1-pc. Unit	N/A	Main tees 48" o.c.
USG Drywall Suspension Cross Tees	DGLW424	4'	48-pc. carton	192 LF/ctn	Cross tees 16" o.c.
5/8″ USG Sheetrock® Brand Ensemble® Four-Sided Taper™ Panels	ENSPNL120	5/8" x 4 'x 10'	26-pc. unit	10'-1040 sq. ft./unit	Gypsum panel highly engineered to perform like an acoustical ceiling panel
1″ USG Ensemble® High-NRC Backer Panels	ENSHINRC	1" x 15.5" x 47.75"	4-pc. unit	21.33 sq. ft./ carton	Acoustical base mat for High-NRC/High-CAC
USG Sheetrock® Brand Paper Joint Tape	-	250' roll	20 rolls per carton	5,000 LF/ctn	Specially formulated paper tape
USG Sheetrock® Brand All Purpose Joint Compound	USAPJC	4.5-gal. pail	Single pail 48-pail pallet	216 gal./pallet	Coverage 100 sq. ft./gal. 450 sq. ft./4.5-gal. pail
USG Sheetrock® Brand Joint Compound	ENSCJC	4.5-gal. pail	Single pail 48-pail pallet	216 gal./pallet	Coverage 106 sq. ft./gal. 480 sq. ft./4.5-gal. pail
USG Ensemble <sup>™</sup> Spray-Applied Base Finish, White, Custom Colors.	ENSSPRAF	4.5-gal. pail	Single pail 48-pail pallet	216 gal./pallet	Coverage 160-200 sq. ft./4.5-gal. pail

#### **USG ENSEMBLE<sup>®</sup>** ACOUSTICAL DRYWALL COLOR PROGRAM

Custom Color Matching - Specifier to provide a color number from one of the following: 1.

Download SC5075 at usg.com/ensemble

Download SC5048 at usg.com/ensemble

ASTM E84 and CAN/ULC S102 surface-burning characteristics

ASTM E1264 Classification

Type XX – Gypsum, Pattern G

Total System weight 3.2 lb/ft<sup>2</sup>

Flame Spread: 25 or less

Smoke developed: 50 or less

- .
- Benjamin Moore® Sherwin-Williams® .

**Design Guide** 

Fire Class A

Maintenance

Weight

Class A

- PANTONE®
- 2. Request customer color samples through your local USG Ensemble® sales representative.

Recommended Instructions

- 3. Allow three weeks to receive custom color sample.
  - 4. Once the color sample is approved and the order is placed by the purchaser, allow three weeks for the custom-colored USG Ensemble™ Spray-Applied Finish to ship with the USG Ensemble® Acoustical Drywall order.
- 5 The USG Ensemble™ Spray-Applied Finish is similar to flat finish paint in sheen. Different sheens are not offered at this time. 6. Certain very deep tone colors or certain very bright colors may not be possible to match. USG will be able to determine at the time of the custom color sample request.

PHYSICA	L DATA
---------	--------

РН	YS	CAL	. DA	IA

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

#### SC3264/rev. 8-23

© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

The trademarks USG, CGC, COMPÄSSO, ENSEMBLE, FOUR-SIDED TAPER, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG and CGC logos, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates. Manufactured by USG Interiors, LLC 550 West Adams Street Chicago, IL 60661

Declare is a trademark of International Living Future Institute The trademark BENJAMIN MOORE is a registered trademark of Benjamin Moore & Co. The trademark DELRAWIN-WILLIAMS is a registered trademark of the The Sherwin-Williams Company. The trademark PANTONE is the property of Pantone LLC.

# Limitations

Minimum order quantity for USG Ensemble™ Spray-Applied Finish is 8 pails.

- 1. For interior ceilings only.
- 2. Not for use in areas subject to continuous high-heat and/or humid conditions.
- 3. The Ensemble® system shown above not for use in return-air plenums.
- Return air ducts shall be installed according to ASHRAE standards and 4. guidelines
- 5. Install according to Section 5 Environmental Conditions listed in ASTM C840
- 6. In order to ensure installed performance, component substitutions should not be permitted
- 7. Vaults minimum bend radius 20' and valley minimum bend radius 10'
- 8. Do not wet the USG Sheetrock® Brand Ensemble® Four-Sided Taper™ Panels

USG Ensemble<sup>™</sup> Spray-Applied Finish or USG Sheetrock<sup>®</sup> Brand Ensemble<sup>®</sup> 9. Four-Sided Taper<sup>™</sup> Panels cannot be painted without negatively affecting acoustical performance

> Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment Read SDS and literature before specification and installation.

