

USG HALCYON™ / HALCYON™ ECO ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

USG Halcyon™ Acoustical Panels
with ClimaPlus™ Performance, and
USG Donn® Brand Identitee® DXI™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050



Limited color options available.
See Ceiling Solutions Color
Program for details.

FEATURES AND BENEFITS

- Exception noise reduction with NRC values up to 1.00.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish.
- Impact and scratch resistant.
- Coordinates visually with USG Mars™ for open/closed-plan applications.
- Compatible with USG Logix™ Integrated Ceiling Systems.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Balanced Acoustics. High NRC & High CAC with backer options.
- Halcyon™ ECO is part of the Ecoblueprint portfolio – meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.
- Halcyon™ ECO is manufactured with a plant-based binder.
- Halcyon™ ECO is GREENGUARD Gold Certified for low emitting performance.

APPLICATIONS

- Open-plan offices
- Indirect lighting
- Libraries
- Media rooms
- Waiting rooms (addresses HIPAA standards)

SUBSTRATE

- Fiberglass

Fine-Textured Panel

USG HALCYON™/HALCYON™ ECO ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL.COM/GG
UL 2818



Declare® Labels on select products, see usg.com for more details and documentation.

UL Classified

Edge	Panel Size ²	Fire Rating	Item No.	NRC	CAC Min.	LR ³	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ <input type="checkbox"/>	2'x2'x3/4"	Class A	97221	0.90	20	0.90	White	A, B, C	—		38%	\$\$\$\$
	2'x4'x3/4"	Class A	97241	0.90	20	0.90	White	A, B	—		38%	\$\$\$\$
	2'x2'x1"	Class A	98221	0.95	20	0.90	White	A, B, C	—		40%	\$\$\$\$
	2'x2'x1" Foil-Back	Class A	88221	0.90	27	0.90	White	A, B, C	—		37%	\$\$\$\$
	2'x4'x1"	Class A	98241	0.95	20	0.90	White	A, B	—		40%	\$\$\$\$
	2'x4'x1" Foil-Back	Class A	88223	0.90	27	0.90	White	A, B	—		37%	\$\$\$\$
	30"x30"x1"	Class A	98331	0.95	20	0.90	White	A, B	—		40%	\$\$\$\$
	30"x60"x1"	Class A	97266	0.95	20	0.90	White	A, B	—		40%	\$\$\$\$
	2'x4'x1-1/2"	Class A	99241	1.00	25	0.90	White	A, B	—		42%	\$\$\$\$
	2'x4'x1-1/2" Foil-Back	Class A	88224	0.95	30	0.90	White	A, B	—		39%	\$\$\$\$
	2'x2'x1-1/2"	Class A	99221	1.00	25	0.90	White	A, B, C	—		42%	\$\$\$\$
	2'x2'x1-1/2" Foil-Back	Class A	97356	0.95	30	0.90	White	A,B,C	—		39%	\$\$\$\$
SQ <input type="checkbox"/>	2'x2'x1"	Class A	97312	0.95	20	0.90	White	A, B, C	Low		34%	\$\$\$\$
	2'x4'x1"	Class A	97313	0.95	20	0.90	White	A, B	Low		34%	\$\$\$\$
	4'x4x1"	Class A	97314	0.95	20	0.90	White	A, B	Low		34%	\$\$\$\$

ClimaPlus™ Warranty Performance⁴
Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

USG HALCYON™
ACOUSTICAL PANELS

USG HALCYON™ ECO
ACOUSTICAL PANELS
Plant-Based Binder

USG HALCYON™/HALCYON™ ECO ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgdesignstudio.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)

Declare® Labels on select products, see usg.com for more details and documentation.



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/GG UL 2818

30 YEAR LIMITED SYSTEM WARRANTY
• No Visible Sag
• Mold/Mildew Protection



10 YEAR AVAILABILITY
78575, 78775, 78975, 78575, 78775



UL Classified

Edge	Panel Size ²	Fire Rating	Item No.	NRC	CAC Min.	LR ³	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SL	2'x2'x1"	Class A	98223	0.95	20	0.90	White	D	—	□	40%	\$\$\$\$
	2'x2'x1" Foil-Back	Class A	88225	0.90	27	0.90	White	D	—	□	37%	\$\$\$\$
	2'x4'x1"	Class A	98243	0.95	20	0.90	White	D	—	□	40%	\$\$\$\$
	2'x4'x1" Foil-Back	Class A	88226	0.90	27	0.90	White	D	—	□	37%	\$\$\$\$
	30"x30"x1"	Class A	98333	0.95	20	0.90	White	D	—	□	40%	\$\$\$\$
	30"x60"x1"	Class A	99270	0.95	20	0.90	White	D	—	□	40%	\$\$\$\$
	2'x2'x1-1/2"	Class A	99223	1.00	25	0.90	White	D	—	□	42%	\$\$\$\$
	2'x2'x1-1/2" Foil-Back	Class A	97357	0.95	30	0.90	White	D	—	□	39%	\$\$\$\$
	2'x4'x1-1/2" Foil-Back	Class A	97358	0.95	30	0.90	White	D	—	□	39%	\$\$\$\$
SL	2'x2'x1"	Class A	97315	0.95	20	0.90	White	D	Low	□	34%	\$\$\$\$
	2'x4'x1"	Class A	97316	0.95	20	0.90	White	D	Low	□	34%	\$\$\$\$
	4'x4x1"	Class A	97317	0.95	20	0.90	White	D	Low	□	34%	\$\$\$\$

USG HALCYON™ ACOUSTICAL PANELS

USG HALCYON™ ECO ACOUSTICAL PANELS
Plant-Based Binder

ClimaPlus™ Warranty Performance⁴
Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

USG HALCYON™/HALCYON™ ECO ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:
UL.COM/GG
UL 2818

30 YEAR LIMITED SYSTEM WARRANTY
• No Visible Sag
• Mold/Mildew Protection



10 YEAR AVAILABILITY
76975, 76775, 76975, 78575, 78775



ECOBUEPRINT

Declare.

Declare® Labels on select products, see usg.com for more details and documentation.

UL Classified

Edge	Panel Size²	Fire Rating	Item No.	NRC	CAC Min.	LR³	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content¹	Panel Cost
FL	2'x2'x1"	Class A	98225	0.95	20	0.90	White	E, F, G, H	—		40%	\$\$\$\$
	2'x2'x1" Foil-Back	Class A	88227	0.90	27	0.90	White	E, F, G, H	—		37%	\$\$\$\$
	2'x4'x1"	Class A	98245	0.95	20	0.90	White	E, F, G, H	—		40%	\$\$\$\$
	2'x4'x1" Foil-Back	Class A	97368	0.90 ⁷	27 ⁸	0.90	White	E, F, G, H	—		37%	\$\$\$\$
	30"x30"x1"	Class A	98335	0.95	20	0.90	White	E, F, G, H	—		40%	\$\$\$\$
	30"x60"x1"	Class A	98336	0.95	20	0.90	White	E, F, G, H	—		40%	\$\$\$\$
	2'x2'x1-1/2"	Class A	99225	1.00	25	0.90	White	E, F, G, H	—		42%	\$\$\$\$
	2'x2'x1-1/2" Foil-Back	Class A	97359	0.95 ⁷	30 ⁸	0.90	White	E, F, G, H	—		39%	\$\$\$\$\$
FL	2'x2'x1"	Class A	97318	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$
	2'x4'x1"	Class A	97319	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$
	2'x5'x1"	Class A	97340	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$
	2'x6'x1"	Class A	97341	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$
	2'x8'x1"	Class A	97342	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$
	4'x4'x1"	Class A	97320	0.95	20	0.90	White	E, F, G, H	Low		34%	\$\$\$\$

ClimaPlus™ Warranty Performance*
Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C ⁵ USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Fineline® DXF™	G USG Fineline® 1/8 DXFF™	H USG Identitee® DXI™

PHYSICAL DATA/ FOOTNOTES

Product literature
Data sheet: SC2365

ASTM E1264 classification
ASTM E1264-22 Type XII, Form 2, Pattern E & G
ASTM E1264-23 Type B, Form B2, Pattern E & G

ASTM E84 and CAN/ULC S102 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Online tools
usgdesignstudio.com or
cgcdesignstudio.com

Weight
0.28 lb./sq. ft. (3/4" panels)
0.40 lb./sq. ft. (1" panels)
0.59 lb./sq. ft. (1-1/2" panels)

Thermal resistance
R-3.3 (3/4" panels),
R-4.4 (1" panels)
R-6.6 (1-1/2" panels)

Maximum backloading
See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.

Treating field-cut reveal edges
All field-cut edges "exposed to view" should be colored to match the factory finish. USG Halcyon™ Touch-up Edge Paint is recommended when perimeter field cuts expose the substrate.

Metric sizes available
Contact sales for minimum quantities and lead times.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
 - Custom-size panels available. Please contact your USG or CGC sales representative for details.
 - LR values are shown as averages.
 - For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).
 - Maximum 2'x2' with SQ edge panels.
 - Select custom color panels are available in limited sizes and edge profiles. Minimum order quantities apply. Please contact your local sales representative for availability, pricing, minimum order quantities and lead times.
 - Tested in accordance with ASTM C423 in USG Acoustical Test Facility (NVLAP Lab Code: 200132-0); not UL classified for acoustics.
 - Tested in accordance with ASTM E1414 in USG Acoustical Test Facility (NVLAP Lab Code: 200132-0); not UL classified for acoustics.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2365/rev. 8-23
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, HALCYON, IDENTITEE, LOGIX, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

