

USG
Interior
Panel &
Finishing
Solutions

FIRECODE® X (UL TYPE ULIX)

FIRECODE® X (UL TYPE ULIX)

**BUILT FOR PERFORMANCE.
PRINTED FOR SIMPLICITY.**

[usg.com](https://www.usg.com)



IT'S YOUR WORLD. BUILD IT.®

At USG, our commitment to manufacturing the highest quality wallboard is only matched by our dedication to fostering job site efficiency and safety. It's the reason we print performance characteristics and Underwriters Laboratories Inc. (UL) Type Designations in the field of our panels. By making them more identifiable to contractors and installers, you can be sure that you quickly find the information you need to get the job done right the first time.

Printing in the field also makes it easier for code officials to identify the panels by their designation. Even after the joints are finished, this will confirm that the right panels are installed in the correct locations, ensuring the integrity of the building and the safety of its occupants.

	PRODUCT NAME	PANEL THICKNESS	FIELD PRINT MESSAGE - REPEATED EVERY 4 FEET, 12-15 INCHES FROM THE LONG EDGE	FIRE RESISTANCE	ENHANCED FIRE RESISTANCE	MOLD RESISTANCE	MOISTURE RESISTANCE	SAG RESISTANCE	ABUSE RESISTANCE	IMPACT RESISTANCE
SUSTAINABLE PANELS	USG Sheetrock® Brand EcoSmart Panels	1/2 in.	SAG-RESISTANT	—	—	—	—	▾	—	—
	USG Sheetrock® Brand EcoSmart Panels Firecode 30®	5/8 in.	FIRECODE 30® (UL TYPE FC30)	▾	—	—	—	—	—	—
	USG Sheetrock® Brand EcoSmart Panels Firecode® X	5/8 in.	FIRECODE® X (UL TYPE ULIX)	▾	▾	—	—	—	—	—
LIGHTWEIGHT PANELS	USG Sheetrock® Brand UltraLight Panels	1/2 in.	SAG-RESISTANT (ICC ESR-3365)	—	—	—	—	▾	—	—
	USG Sheetrock® Brand UltraLight Panels Mold Tough®	1/2 in.	MOLD-RESISTANT	—	—	▾	▾	—	—	—
	USG Sheetrock® Brand UltraLight Panels Mold Tough® Firecode® X¹	5/8 in.	MOLD-RESISTANT FIRECODE® X (UL TYPE ULX or ULIX)	▾	▾	▾	▾	—	—	—
	USG Sheetrock® Brand UltraLight Panels Firecode® X¹	5/8 in.	FIRECODE® X (UL TYPE ULX)	▾	—	—	—	—	—	—
FIRE-RESISTANT PANELS	USG Sheetrock® Brand Firecode® C Panels	1/2 in. and 5/8 in.	FIRECODE® C (UL TYPE C)	▾	▾	—	—	—	—	—
	USG Sheetrock® Brand Ultracode® Core Panels	3/4 in.	ULTRACODE® (UL TYPE ULTRACODE)	▾	▾	—	—	—	—	—
	USG Sheetrock® Brand Firecode® X Panels	5/8 in.	FIRECODE® X (UL TYPE SCX)	▾	—	—	—	—	—	—
MOLD-RESISTANT PANELS	USG Sheetrock® Brand Mold Tough® Firecode® X Panels	5/8 in.	MOLD-RESISTANT FIRECODE® X (UL TYPE SCX)	▾	—	▾	▾	—	—	—
	USG Sheetrock® Brand Mold Tough® Firecode® C Panels	1/2 in. and 5/8 in.	MOLD-RESISTANT FIRECODE® C (UL TYPE C)	▾	▾	▾	▾	—	—	—
	USG Sheetrock® Brand Glass-Mat Panels Mold Tough®	1/2 in.	MOLD-RESISTANT	—	—	▾	▾	—	—	—
	USG Sheetrock® Brand Glass-Mat Panels Mold Tough® Firecode® X	5/8 in.	MOLD-RESISTANT FIRECODE® X (UL TYPE SGX)	▾	—	▾	▾	—	—	—
	USG Sheetrock® Brand Mold Tough® Ultracode® Core Panels	3/4 in.	MOLD-RESISTANT ULTRACODE® (UL TYPE ULTRACODE)	▾	▾	▾	▾	—	—	—
PLASTER-BASE PANELS	USG Sheetrock® Brand Sag-Resistant Interior Ceiling Gypsum Base Imperial®	1/2 in.	SAG-RESISTANT	—	—	—	—	▾	—	—
	USG Sheetrock® Brand Gypsum Base Imperial®, Firecode® X	5/8 in.	FIRECODE® X (UL TYPE IP-X1)	▾	—	—	—	—	—	—
	USG Sheetrock® Brand Gypsum Base Imperial®, Firecode® C	1/2 in. and 5/8 in.	FIRECODE® C (UL TYPE IP-X2)	▾	▾	—	—	—	—	—
ABUSE-RESISTANT PANELS	USG Sheetrock® Brand AR Firecode® X Panels	5/8 in.	ABUSE-RESISTANT FIRECODE® X (UL TYPE AR)	▾	—	—	—	—	▾	—
	USG Sheetrock® Brand Mold Tough® AR Firecode® X Panels	5/8 in.	MOLD-RESISTANT ABUSE-RESISTANT FIRECODE® X (UL TYPE AR)	▾	—	▾	▾	—	▾	—
	USG Sheetrock® Brand Glass-Mat Panels Mold Tough® AR	5/8 in.	MOLD-RESISTANT ABUSE-RESISTANT FIRECODE® X (UL TYPE AR)	▾	—	▾	▾	—	▾	—
	USG Sheetrock® Brand Mold Tough® VHI Firecode® X Panels	5/8 in.	MOLD-RESISTANT IMPACT-RESISTANT FIRECODE® X (UL TYPE AR)	▾	—	▾	▾	—	▾	▾
	USG Sheetrock® Brand Glass-Mat Panels Mold Tough® VHI	5/8 in.	MOLD-RESISTANT IMPACT-RESISTANT FIRECODE® X (UL TYPE AR)	▾	—	▾	▾	—	▾	▾
SHEATHING PANELS	USG Sheetrock® Brand Gypsum Sheathing	1/2 in.	MOISTURE-RESISTANT	—	—	—	▾	—	—	—
	USG Sheetrock® Brand Gypsum Sheathing Firecode® X	5/8 in.	FIRECODE® X (UL TYPE SHX)	▾	—	—	▾	—	—	—
	USG Securock® Brand Glass-Mat Sheathing	1/2 in.	THIS SIDE OUT-COATED MAT	—	—	▾	▾	—	—	—
	USG Securock® Brand Glass-Mat Sheathing Firecode® X	5/8 in.	5/8": THIS SIDE OUT-COATED MAT FIRECODE® X (UL TYPE USGX)	▾	—	▾	▾	—	—	—
	USG Securock® Brand UltraLight Glass-Mat Sheathing	1/2 in.	1/2": THIS SIDE OUT-ULTRALIGHTWEIGHT CORE	—	—	▾	▾	—	—	—
	USG Securock® Brand UltraLight Glass-Mat Sheathing Firecode® X	5/8 in.	5/8": THIS SIDE OUT-ULTRALIGHTWEIGHT FIRECODE® X (UL TYPE USGX)	▾	—	▾	▾	—	—	—

Notes
1. UL Type ULX panels are available in New England, Mid-Atlantic, South Atlantic and East Central regions.

CONTACT INFORMATION

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

PRODUCT INFORMATION

See usg.com for the most up-to-date
product information.

CUSTOMER SERVICE

800 621-9523

TECHNICAL SERVICE

800 USG.4YOU (874-4968)

WEBSITES

usg.com
usgdesignstudio.com

NOTE

Products described here may not be available
in all geographic markets. Consult your USG
Company sales office or representative for
information. The information in this document
is subject to change without notice. USG
Corporation assumes no responsibility for any
errors that may inadvertently appear in this
document.

NOTICE

We shall not be liable for incidental and
consequential damages, directly or indirectly
sustained, nor for any loss caused by application
of these goods not in accordance with current
printed instructions or for other than the
intended use. Our liability is expressly limited
to replacement of defective goods. Any claim
shall be deemed waived unless made in writing
to us within thirty (30) days from date it was or
reasonably should have been discovered.

SAFETY FIRST!

Follow good safety and industrial hygiene
practices during handling and installation
of all products and systems. Take necessary
precautions and wear the appropriate personal
protective equipment as needed. Read Safety
Data Sheets and related literature on products
before specification and/or installation.

