



EnerFoam™

Polyurethane Gun Foam System



Dow®

Because of its versatility, EnerFoam has established itself as the premier polyurethane foam available to professionals. EnerFoam is ideal for applications including insulation, hole and crack filling, blocking insects and acoustical sealing (STC 69). EnerFoam's high yield saves professionals both time and money.

PRODUCT FEATURES:

- Replaces up to 40 quart tubes of traditional adhesive
- Fast curing foam can be trimmed in less than one hour
- Unique mechanical valve spring loaded for reuse
- Won't glue shut after use
- Elastic properties
- Contains no solvents and is compatible with EPS foamboard
- Less mudding labor and fewer "nail pops" reduce callbacks
- Minimal expansion



Wind-lock®
Your faithful business companion

1055 Leisz's Bridge Road • Leesport, PA 19533
610-926-6815 • 1-800-872-5625 • Fax: 1-800-854-6614
www.wind-lock.com



EnerFoam™

Polyurethane Gun Foam System

PRODUCT DESCRIPTION

EnerFoam is a polyurethane foam sealant versatile enough for hundreds of applications around homes and commercial buildings.

APPLICATIONS

EnerFoam is ideal for insulation applications, gaps and crack filling, acoustical sealing and as a barrier to pests. Indoor applications include basements and attics filling pipe/duct penetrations, plumbing stacks and shafts, wall cracks and attic hatches. Also used on baseboards, window and door frames, electrical outlets, conduit penetrations and air/heating vents. Outdoor applications include siding edges, electric, gas and A/C penetrations, garage ceiling walls, repair insect damage to trees and dryer vents.

INSTALLATION

Read all instructions and safety information before using any products. Wear gloves, eye protection and work clothes during application.

Surface Preparation: Protect work area with drop cloths or newspapers. Use in a well-ventilated area, with all nearby pilot lights and other sources of ignition shut off.

Storage: When stored at room temperature, can be dispensed in a wide temperature range. Works in outside temperatures of 25–120°F (-4–49°C).

TEST METHODS

- ASTM C557-93 “Adhesives for Fastening Gypsum Wallboard to Wood Framing.”
- CGSB 71.25 “Canadian Drywall and Subfloor Adhesive Standards.”
- CA25-4 “Standard for the Evaluation of Adhesives for Structural Use in the Manufacture of Mobile Homes and Commercial Coaches.”

ADDED BENEFITS

- Great for sealing around windows and doors.
- Professional applicator tool available in three models for access to hard-to-reach places.
- R-value of 5.7. Acoustical rating of 69STC.
- Foam will expand and compress with the shifting of structures from winter to summer. Won't crack like rigid foams.

ORDERING INFORMATION

EnerFoam 24 oz.

PART CODE: W-EF25 (Case of 12)

EnerFoam 32 oz.

PART CODE: W-EF42 (Case of 12)

Straw foam also available. Please call for details.



Distributed by: