

PRODUCT SUBMITTAL

WIRE-BOND

#3200 Panel Anchor



MATERIAL CONFORMANCE

SIZES / FINISHES

SHEET METAL - (Carbon Steel) ASTM A1008 / A1008M

Hot Dip Galvanized after fabrication / Zinc Coating
ASTM A153 / A153M-B2 (1.50 oz per sq ft)

Stainless Steel ASTM 580 / ASTM 580M Type 304
(Type 316 available on special order)



Recycled Content:
Mill Galvanized & Hot Dipped,
82.8% Post-Consumer
17% Post Industrial / Pre-Consumer,

Stainless Steel,
97% Pre-Consumer
V O C Content - 0%

PANEL ANCHOR:

Provides support to standard glass block panels.
Spaced and installed according to specification.

DIMENSIONS: 20 gauge perforated strips, 1-3/4" x 24".

FINISHES:

Hot Dip Galvanized

Stainless Steel

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761
Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449
Mailing Address: P.O. Box 13124 Memphis, TN 38113